

## Product Description

- **Product Code:** SEPLUS10
- **Product Description:** Acoustic mats in Rolls on predominantly ecological basis for the loose installation under laminate, parquet and other hard floorings. Walking noise reduction and footfall sound protection under laminate, parquet and other hard floors. Especially suitable for click-systems. Suited for floor heating systems.
- **Dimensions:** 10000 L x 1000 W x 2,5 TH mm
- **Packaging:** Per roll • 10m<sup>2</sup> (20 kg net). Per pallet. 28 rolls • 280m<sup>2</sup> ( 560 kg net). Rolls in PE-bag with manual instruction taped on the front.
- **Composition:** Permanently elastic underlayment material made of mineral fillers and polyurethane binder based on renewable natural materials, single-sided fleece laminated. CFC-free, No use of ozone-depleting substances, Solvent-free
- **Production process:** The underlay is laid and tailored perpendicular to the laying direction of the coverage. Make sure the edges are flush against each other and tape them with commercial available aluminium adhesive tape. Only for floating installation. Obtain clearance of the floor manufacturers.
- **Installation Instruction:**

## Requirements

Characteristics	Norm	Value	Unit
Footfall sound reduction under 7 mm lam flooring	EPLF standard 021029/ISO 532B	ca 22	sone
Impact sound protection	DIN / ISO 140-8 (laminate flooring 7 mm)	21	dB
Impact sound protection	DIN / ISO 140-8 (parquet flooring 14 mm)	19	dB
Thermal resistance	ISO 2581 / DIN 52616 (without cover)	0,01	m <sup>2</sup> /kw
Permanent pressure resistance	EN 826	100	KN
Vapour barrier	sd-value	> 100	m
Flammability class	DIN 4102	B3	
Max deformation		0,13	mm
Compressive Strength	EN 1606	60	kPa

## Other technical data



In case of fire:	Harmless for health - IFF-Proof report-NR.WP-570-2002
Floor heating:	Suitable for laying on hot water floor heating
Cover material:	White fleece profile back/ aluminium composite film/ vapour barrier foil
Carrier material:	PET-foil ca. 12µ
Disposal:	Rubbish tip and incinerator
Waste code number:	EAK-Nr. 170604
Environment	The following materials are NOT contained: plasticizer, asbestos, formaldehyde, cadmium and other, heavy metals, halogens
Storage conditions	Store in dry ventilated place, at room temperature, protect from direct sunlight

