

DECLARATION OF PERFORMANCE

Strength graded structural timber

Construction product

Strength graded structural timber which has been planed by the producer below and fulfills the requirements according to EN 14081-1:2005+A1:2011. For further or more detailed information on the delivered product, in addition to what is given below, see information on the packaging or in possible accompanying commercial document.

Intended use of the construction product

For load-bearing purposes in construction works designed according to Eurocode 5 (EN 1995) and for other uses where the strength and stiffness of the structure is essential.

Producer

Company: Wood Support Westermarck & Säily AB
 Address: Lindverken
 661 93 Säffle
 Sweden
 Telephone: +46 533-10666
 E-mail: info@woodsupport.se
 Web site: www.woodsupport.se

System of assessment and verification of constancy of performance of the construction product

System 2+.

Certification

The notified body SP Technical Research Institute of Sweden (identification number 0402) has performed an initial inspection of the manufacturing plant and of the factory production control and performs continuous surveillance, assessment and evaluation of our factory production control. SP has issued EC Certificate of Factory Production Control No 0402 – CPR – SC02221-10.

Declared performance

Performance for strength graded structural timber in conformity with the harmonized European standard EN 14081-1:2005+A1:2011 Timber structures – Strength graded structural timber with rectangular cross section – Part 1: General requirements.

Essential characteristics

Declared performance

Species/species group	WPPA: spruce (<i>Picea abies</i>) and pine (<i>Pinus sylvestris</i>)
Growth area	NNE Europe (Northern and North Eastern Europe)
Range of thickness (fire resistance)	31 – 110 mm
Range of width (fire resistance)	60 - 300 mm

Surface finish	Planed
Dry or wet graded	Dry graded
Grading machines	Dynagrade
Strength, stiffness and density	According to EN 338: C30, C24, C18, C16 and C14
Durability	4 (according to EN 350-2)
Reaction to fire	D-s2, d0 (according to EN 14081-1, Table C.1)
Release of dangerous substances	No dangerous substance to be declared

That the performance for our construction product strength graded structural timber is in accordance with the declared performance given above is certified:

Säffle 2015-12-21.....
(place and date of issue)

Wood Support Westermarck & Säily AB


.....
(signature)

Jarmo Säily
Managing Director
JARMO SÄILY.....
(name and function)