






BESKRIVELSE			
Total tykkelse	EN 428	mm	2.00
Vekt	EN 430	g/m ²	3300
Bredde	EN 426	cm	200
Lengde	EN 426	ml	20
KLASSIFISERING			
Norm		-	EN 649
Europaklasse	EN 685	-	34 - 43
K klasse	-	klasse	K5
Brannklassifisering	EN 13501-1	klasse	B _{fl} -s1
Kritisk strålingsperiode	ASTM E 648	klasse	class I
Elektrisk motstand	EN 1081	Ohm	10 ⁶ ≤ Rt ≤ 10 ⁸
	IEC 61340-5-1	Ohm	10 ⁶ ≤ Rt ≤ 10 ⁹
	ANSI / ESD-S7.1	Ohm	10 ⁶ ≤ Rt ≤ 10 ⁸
Elektrostatisk oppladning	EN 1815	kV	< 2
	IEC 61340-4-5	V	< 100
TESTVERDIER			
Slitestyrke	EN 660.2	mm ³	≤ 7.5
Slitasjegruppe	EN 649	-	M
Type Binder content	ISO 10581	type	II
Dimensjonsstabilitet	EN 434	%	≤ 0,40
Inntrykksfasthet	EN 433	mm	~ 0,03
Rullende stolhjul (typen W)	EN 425	-	OK
Varmemotstand	EN 12 524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Kjemikaliebestandighet	EN 423	-	OK
MARQUAGE CE			
	EN 14041	-	  
		-	 B _{fl} -s1