

BESKRIVELSE

Total tykkelse	EN 428	mm	2.00
Tykkelse slitesjikt	EN 429	mm	1.02
Vekt	EN 430	g/m ²	2580
Bredde	EN 426	cm	200
Lengde	EN 426	lm	20





KLASSIFISERING

Norm	-	-	EN 649
Europaklasse	EN 685	-	34 - 43
Brannklassifisering	EN 13 501-1	klasse	B _{fl} -s1
Elektrostatisk oppladning	EN 1815	kV	< 2
Friksjon, våt	DIN 51 130	klasse	R9

TESTVERDIER

Slitestyrke	EN 660.2	mm ³	≤ 2.0
Slitasjegruppe	EN 649	gruppe	T
Type Binder Content	ISO 10582	type	I
Dimensjonsstabilitet	EN 434	%	≤ 0.40
Inntrykksfasthet	EN 433	mm	≤ 0.10
Målresultat	-	mm	~ 0.03
Trinnlydsdemping	EN ISO 717-2	dB	6
Rullende stolhjul (typen W)	EN 425	-	OK
Varmemotstand	EN 12 524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Kjemikaliebestandighet	EN 423	-	OK
Behandling	-	-	Sanosol®
Overflatebehandling	-	-	Protocolsol®

CE MARKING

	EN 14041	-	  
--	----------	---	---



-