

Gulvtype

EN ISO 26986 **Vinylgulv**

Sliteklasse

EN ISO 10874



Klasse

23

32

Beskrivelse



EN ISO 24346
Totaltykkelse EN 428

2,40 mm



EN ISO 24340
Slitesjikt EN 429

0,35 mm



EN ISO 24341
Dimensjon EN 426

25 m
4+3+2m



EN ISO 23997
Total vekt EN 430

1,730 kg/m²



EN660-2
Slitasjegruppe
Klasse EN 649

≤2mm³



ISO 4918
EN 425
Trinsehjul

OK



EN ISO 717/2
Trinnlyd

ca. 16 dB



EN ISO 24343-1
EN 433
Inntrykksmerker

≤ 0,20 mm

Annen informasjon



ISO 105/B02
Lysbetandighet

≥ 6



Sklihemming
EN 13893
DIN 51130

μ ≥ 0,30
R10



Brannklasse
EN 13501-1 **Cfl-s1**
Limt på trefiberplater
Report N° : **RA14-0232**



EN ISO 23999
EN 434
Dimensjon

≤ 0,40 %



Resirkulering

OK



EN 1815
Statisk opplading **≤ 2 kV**



EN ISO 10456
(EN 12524)
Varmemotstand

0,06 m²/kW



**Kjemikalie
bestandighet**

OK

