

**PRODUCT
DATA SHEET**

STARFLOOR CLICK 50 Tiles

November 2012

Type of flooring

EN 649

Compact Resilient Flooring

Class of use

EN 685



23



32

Class

Description



EN 428

5,00 mm



EN 429

0,50 mm



EN 660-2

Abrasion group

**T
≤ 2,00 mm³**



EN 430

9,2 kg/m²



EN 427

Length + Width

**60,3 cm
31 cm**



EN 425

Castor chair
Fully adhered

OK



EN ISO 717/2

Impact sound
absorption

5 dB



EN 433

Static
indentation

≤ 0,08 mm

Optional Characteristics



ISO 105/B02

Light fastness

≥ 6



EN 1815

Static electrical
propensity

≤ 2 kV



Fire Classification

EN 13501-1

Bfl-s1

Report N° :



EN 434

Dimensional
stability

**≤ 2 mm
< 0,10 %**



Recyclable

OK



EN 12524

Thermal resistance

0,04 m² k/W



Slip resistance

DIN 51130

En 13893

**R9
μ≥0,30**



EN 14041 : 2004

Manufactured in PRC by
TARKETT

STARFLOOR
CLICK 50

TARKETT
BALANCED
CHOICE

82 %

Natural

100 %

Recyclable



*TVOC AT 28 DAYS