

BESKRIVELSE

Total tykkelse	EN 428	mm	2.40
Tykkelse slitesjikt	EN 429	mm	
Vekt	EN 430	g/m ²	3700
Flisstørrelse	EN 427	mm	305 x 610
Staverstørrelse	EN 427	mm	
Antall fliser/pakke	-	-	20
Antall staver/pakke	-	-	





KLASSIFISERING

Norm	-	-	EN 649
Europaklasse	EN 685	-	34 - 43
Brannklassifisering	EN 13 501-1	klasse	Bfl-s1
Elektrostatisk oppladning	EN 1815	kV	< 2
Friksjon, våt	DIN 51 130	klasse	R10

TESTVERDIER

Slitestyrke	EN 660.2	mm ³	≤ 4.0
Slitasjegruppe	EN 649	gruppe	P
Type Binder content	ISO 10582	type	II
Dimensjonsstabilitet	EN 434	%	≤ 0.25
Inntrykksfasthet	EN 433	mm	≤ 0.10
Rullende stolhjul (typen W)	EN 425	-	OK
Varmemotstand	EN 12524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Kjemikaliebestandighet	EN 423	klasse	OK
Overflatebehandling	-	-	PUR+

CE MARKING

	EN 14041	-	  
		-	