

**PRODUCT
DATA SHEET**

Exclusive 240
Vinyl Collection

December 2014

Type of flooring

EN ISO 26986 **Vinyl Floorcovering**

Class of use

EN ISO 10874



23



32

Class

Description



EN ISO 24346
(Previously EN 428)

2,40 mm



EN ISO 24340
(Previously EN 429)

0,35 mm



EN ISO 24341
(Previously EN 426)

25 m
4+3+2m



EN ISO 23997
(Previously EN 430)

1,730 kg/m²



EN660-2
Abrasion resistance **≤2mm³**
(Class T according to EN 649)



ISO 4918 **OK**
(EN 425)
Castor wheel test



EN ISO 717/2 **ca. 16 dB**
Impact sound absorption



EN ISO 24343-1 **≤ 0,20 mm**
(Previously EN 433)
Static indentation

Other Characteristics



ISO 105/B02
Light fastness

≥ 6



Slip resistance
EN 13893
DIN 51130

μ ≥ 0,30
R10



Fire Classification
EN 13501-1 **Cfl-s1**
(glued over wooden panel)
Report N° : **RA14-0232**



EN ISO 23999
(Previously EN 434)
Dimensional stability

≤ 0,40 %



Recyclable

OK



EN ISO 10456
(EN 12524)
Thermal resistance
for underfloor heating

0,06 m²/kW



**Chemical
resistance**

OK



EN 1815 **≤ 2 kV**
Static electrical
propensity



Exclusive 240
No. 0004-0023-DoP-2015-01
<http://www.home.tarkett.com>
Manufactured by: Tarkett Holding
GmbH - 122, Granastrasse
54329 Konz, Germany
EN 14041:2004

**EXCLUSIVE
240**

100 %
Recyclable

**PTHALATE
FREE
Technology***

< 100µg/m³
Better Indoor
Air Quality
*TVOC AT 28 DAYS

ÉMISSIONS DANS L'AIR INTÉRIEUR
A+
A+ A B C

Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.