

**PRODUCT  
DATA SHEET**

# Tarkett Design 200

## Vinyl Collection 2014 - 2015

January 2014

**Type of flooring**

EN 653

**Vinyl Floorcovering**

**Class of use**

EN 685



23



32



41

Class

**Description**



EN 428

2,00 mm



EN 429

0,40 mm



EN 426

25 m  
4+3+2m



EN 430

2,150 kg/m<sup>2</sup>



EN 660-2

Abrasion group

T



EN 425

Castor chair  
Fully adhered

OK



EN ISO 717/2

Impact sound  
absorption

ca. 13 dB



EN 433

Static  
indentation

≤ 0,10 mm

**Other Characteristics**



ISO 105/B02  
Light fastness

≥ 6



Slip resistance  
EN 13893  
DIN 51130

≥ 0,30 μ  
R10



Fire Classification  
EN 13501-1  
Report N° :

Bfl-s1  
RA10-0254



EN 434  
Dimensional  
stability

≤ 0,40 %



Recyclable

OK



EN 1815  
Static electrical  
propensity

≤ 2 kV



EN 12524  
Thermal resistance  
for underfloor heating

0,02 m<sup>2</sup>/kW



Chemical  
resistance

OK



**Exclusive 200**  
No. 0131-0005-DoP-2013-07  
<http://www.home.tarkett.com>  
Manufactured by: Tarkett GDL SA  
2, Op der Sang  
L-9979 Lentzweiler - Luxembourg



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.