

**PRODUKT
DATABLAD**

WATERPROOF DESIGN GULV 3m

TopClean PUR-reinforced
Kolleksjon 2014 - 2016

November 2014

Gulvtype

EN 649

Vinylgulv

Sliteklasse

EN 685



23



32



41

Klasse



EN 428

Total tykkelse

2,00 mm



EN 429

Slitesjikt

0,40 mm



EN 426

Dimensjon

**15 - 25 m
3m**



EN 430

Total vekt

2,150 kg/m²



EN 660-2

Slitasjegruppe

T



EN 433

Inntrykksmerker

≤ 0,10 mm

Aquarelle - slitesjikt 0,4 mm

24554001 Aquarelle Istanbul M. Grey

24554002 Aquarelle Istanbul D. Grey

24554005 Aquarelle Ceramica Grey

24554004 Aquarelle Ceramica Beige

24554003 Aquarelle Square Black&White

5619034 Waterproof Authentic Slate Beige

5619035 Waterproof Authentic Slate Black

5619011 Waterproof Anthia Black

5715004 Waterproof Moda Grey

Annen informasjon



ISO 105/B02

Lysbestandighet

≥ 6



EN 13501-1

Brannklasse

Bfl-s1



EN 12524

Varmemotstand

0,02 m²/kW



EN 13893

DIN 51130

Sklihemming

≥ 0,30 μ

R9



EN 1815

Statisk oppladning

≤ 2 kV




Aquarelle Floor 3m

0131-0005-DoP-2013-07
www.tarkett.se

Made by: Tarkett GDL SA.

Lentzweiler - LUXEMBURG



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.