

# Omnisports SPEED



## KEY POINTS

### Description :

Vinyl sports floor covering over fibreglass mat with PVC foam backing. Sanitized® (anti-bacterial coating). Protected with Top Clean XP® (dirty-resistant treatment for ease of maintenance)

### Type of installation :

- Glued Installation

### Surface Texture :

Sorrent

### Compatible Installation :

Association possible with a sub construction (Lumaflex type)

### Installation instructions and maintenance guide :

On request

### Dimensions (EN 426/EN 427) :



2 m



20.5 lm or 23 lm

### Total thickness (EN 428/EN 429) :



3.45 mm (± 0,15mm)

### Total weight (EN 430) :



3.295kg/sqm (± 500g)

EN 14041 : 2004



-collé sur support béton



-collé sur panneau de bois



97

Fabriqué à  
Tarkett Sedan SAS  
2 avenue François Sommer  
08200 SEDAN

OMNISPORTS SPEED

EN

651

Classification according to EN 685



Properties	Standard	Omnisports SPEED
<b>Vinyl Indoor sports flooring with elastic point area deformation</b>		
<b>must be installed on a sub-construction to reach the requirements of the EN 14 904 standard</b>		
<b>Sports properties</b>		
Friction	EN 13036-4	97
Shock Absorption %	EN 14 808	6
Vertical deformation	EN 14 809	0.37
Vertical ball rebound	EN 12235	98%
Specular Gloss	EN ISO 2813	15,6%

Classification		
Reaction to fire	EN 13501-1	Clf-S1
Formaldehyde	EN 717-1	No Formaldehyde
	EN 717-2	
Pentachlorophenol	EN 12673	No pentachlorophenol

Technical characteristics		
Wear Layer	EN 429	0.65 mm
Abrasion	EN ISO 5470-1	0.124 g
Resistance to indentation	EN 1516	0.18mm
Behaviour under a rolling load	EN 1569	1mm
Resistance to impacts	EN 1517	No degradation

Specific characteristics					
Surface treatment	Anti bacteria and anti fungus treatment + Anti bacteria and anti fungus treatment				 
Maintenance					With Dynatech Trophy
Available 11 plain colours 4 wooden patterns	Yellow	Orange	Red	Grey	
	Forest Green	Royal Blue	Field Green	Teal	
	Sky Blue	Black	Mint Green		
	Maple	Beech	Oak Classic	Oak Gunstock	
<b>Compatible slabs:</b> Concrete, asphalt screed, anhydrite screed or Lumaflex sub construction. Any deviation of the slab must be corrected prior installation (6mm under a 3m straight edge). We reserve the right to modify these specifications without, however, affecting their compliance with standards.					

**TARKETT BALANCED CHOICE**

42,9 %  
Natural

100%  
26%  
Recyclable  
Recycled content

**Better Indoor Air Quality**  
\*TVOC AT 28 DAYS  
< 100 µg/m³

Tarkett France – 2, rue de l'Égalité – 92748 Nanterre cedex – TÉL. +33(0)1 41 20 40 40 – FAX +33(0)1 41 20 47 05 – info@tarkett.com

S.A.S au capital de 30800000 euros – RCS Nanterre 410 081640

www.tarkett-sports.com



THE ULTIMATE SURFACE EXPERIENCE

V1 30/04/2011