

**PRODUCT
DATA SHEET**

AQUARELLE FLOOR 2 m

TopClean PUR-reinforced
Collection 2014 -2016

November 2013

Type of flooring

EN 649

Vinyl Floorcovering

Class of use

EN 685



23



31

Class



EN 428

Total thickness

1,500 mm



EN 429

Wear layer thickne

0,35 mm



EN 426

Dimension

18- 25 m
2m



EN 430

Total weight

2 400 kg/m²



EN 660-2

Abrasion group

T



EN 433

Static
indentation

≤ 0,10 mm

Other Characteristics



ISO 105/B02

Light fastness

≥ 6



EN 1815

Static electrical
propensity

≤ 2 kV



EN 12524

Thermal resistance
for underfloor heating

0,02 m²/kW



EN 13501-1

Fire Classification

Bfl-s1



Slip resistance

EN 13893

≥ 0,30 μ

DIN 51130

R9



Aquarelle Floor 3 m

0131-0005-DoP-2013-07
www.tarkett.se

Made by: Tarkett GDLSA.
Lentzweiler - LUXEMBURG

EN 14041:2004



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.