

**PRODUCT
DATA SHEET**

Texstyle

Vinyl Collection 2014 - 2016

January 2014

Type of flooring

EN 653

Vinyl Floorcovering

Class of use

EN 685



23



32

Class

Description



EN 428

2,80 mm



EN 429

0,35 mm



25m
4+3+2m



EN 430

1, 880 kg/m²



EN 660-2

Abrasion group

T



EN 425

Castor chair
Fully adhered

OK



EN ISO 717/2

Impact sound
absorption

ca. 19 dB



EN 433

Static
indentation

≤ 0,20 mm

Optional Characteristics



ISO 105/B02
Light fastness

≥ 6



Slip resistance
EN 13893
DIN 51130

≥ 0,30 μ
R10



Fire Classification
EN 13501-1
Report N° :

Cfl-s1
RA10-0252



EN 434
Dimensional
stability

≤ 0,40 %



Recyclable

NO



EN 1815
Static electrical
propensity

≤ 2 kV



EN 12524
Thermal resistance
for underfloor heating

0,04 m²/kW



Chemical
resistance

OK



Essentials 280T

No. 0004-0016-DoP-2013-04
<http://www.home.tarkett.com>

Manufactured by: Tarkett Holding
GmbH - 122, Granastrasse
54329 Konz, Germany

EN 14041:2004



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.