



WOOD

Salsa
Classic Collection

Product
Datasheet
2015

WOOD

Salsa

Classic Collection



| TECHNICAL INFORMATION | SALSA |
|---|--|
| Thickness | 14 mm |
| Width | 192/194 mm |
| Length | 2028/2281 mm |
| Wearlayer thickness (mm) | app. 3,5 |
| Weight (kg/m ²) | app. 8,0 |
| Taber Abraser/Lacquer's wear resistance* prEN 13696 | |
| abrasion penetration Proteco Lacq.(revs) | >4000 |
| abrasion penetration Proteco Nat.(revs) | >3500 |
| abrasive wear (mg/100revs) | app. 3,5 |
| <i>Data show results with new components according to 2006 update. Results not applicable for stained, brushed or hardwax oiled products.</i> | |
| Reduction of sound weighted index index "footfall" to the room below. | |
| NF EN ISO 140-8 / Acc to NF EN ISO 717-2, ΔL _w in dB with 2 mm Tarkofoam/flex II | 17 |
| Formaldehyde emission EN 13986 | E1 |
| Reaction to Fire EN 13501 | D _{fl} |
| Thermal insulation value (RT m ² K/W) | |
| board only | 0,101 |
| with rag felt | 0,121 |
| with 2 mm Tarkofoam/flex II | 0,141 |
| Installation* | Floating /Glue down |
| Underfloor heating compatible** | Maximum floor surface temperature 27°C with self-regulating under-floor heat system. |

* Contact your flooring supplier for further information.

** Not suitable for Oak Basket Weave or the woodspecies beech and maple.

Salsa Proteco Lacquer / Proteco Natura

| | | |
|----------------------------|-----------------------------------|---------------------|
| TARKETT SUSTAINABILITY TAG | 97 % 97 % Natural Renewable | 100 % Recyclable |
|----------------------------|-----------------------------------|---------------------|

Salsa Proteco Hardwax Oil

| | | |
|----------------------------|-----------------------------------|---------------------|
| TARKETT SUSTAINABILITY TAG | 98 % 98 % Natural Renewable | 100 % Recyclable |
|----------------------------|-----------------------------------|---------------------|

| SALSA | Lacquer 2-lock | Natura 2-lock | Hardwax Oil 2-lock |
|--------------------------------|----------------|---------------|--------------------|
| 3-strip, 14x2281x194 mm | | | |
| Oak Select | • | | |
| Oak Nature | • | • | • |
| Oak Nature brushed | | • | |
| Oak Rustic | | • | |
| Oak Robust | • | • | |
| Oak Robust White | | • | |
| Oak Robust Satin White | | | • |
| Oak Nordic White | • | | |
| Oak Cotton White | | • | |
| Oak Misty Grey | | • | |
| Oak Stone Grey brushed | | • | |
| Oak Khaki Grey brushed | | • | |
| Oak Anthracite Grey | | | • |
| Oak Cumin | | • | |
| Oak Praline brushed | | • | |
| Oak Umber Brown | | | • |
| Oak Black brushed | | • | |
| Beech Nature | • | • | |
| Beech Robust | • | | |
| Ash Nature | • | • | |
| Ash Nature White | | • | |
| Ash White Pearl brushed | • | | |
| Ash Ivory | | • | |
| Ash Smoked | | • | |
| Ash Arctic Grey brushed | | • | |
| Ash Cognac | • | | |
| Ash Cognac brushed | | • | |
| Maple Canadian Nature | • | | |
| Maple Canadian Robust | • | | |
| Birch | • | | |
| Cherry | • | | |
| Cherry Robust | • | | |
| Walnut | • | • | • |
| Walnut Robust (stained) | • | | |

| SALSA FINE LINE | Lacquer 2-lock | Natura 2-lock |
|-----------------------------------|----------------|---------------|
| Multistrip, 14x2281x194 mm | | |
| Oak | • | |
| Oak Grey | | • |
| Oak Brown | | • |

Wood floors, Brinell Hardness (BHN), EN1534

