

# Modern home



Product Data Sheets 2006

WOOD



## TECHNICAL INFORMATION

	Modern Home	Salsa
		Bravo
<b>Thickness (mm)</b>	14	
<b>Width (mm)</b>	190/188	
<b>Length (mm)</b>	1250/2510/2525	
<b>Wearlayer thickness (mm)</b>	~ 3,6	
<b>Weight (kg/m<sup>2</sup>)</b>	8,0	
<b>Taber Abraser/Lacquer's wear resistance*</b>		
ENV 13696/SIS 923509		
abrasion penetration Proteco Lacq.(revs)	>=7000	
abrasion penetration Proteco Nat.(revs)	>=6500	
abrasive wear (mg/100revs)	~3,5	
<b>Reduction of sound weighted index "footfall" to the room below.</b>		
NF EN ISO 140-8/ Acc to NF EN ISO 717-2, ΔL <sub>w</sub> in dB with 3 mm Cellfoam	17	
<b>Formaldehyde emission</b>		
EN 13986	E1	

### Fire safety class

NT Fire 007



Class G\*\*

### Thermal insulation value

(R<sub>T</sub> m<sup>2</sup> K/W)

board only	0,101
with rag felt	0,121
with 3 mm Cellfoam	0,191

### Installation\*\*\*

Floating/Glue down

### Underfloor heating compatible\*\*\*\*

Low temperature (max tempature 27°C) , water-borne system or self-regulating electrical system.

\* Method not applicable for brushed products due to the structured surface

\*\* Number of approval 4514/86. Floorcovering of class G on noncombustible material or on combustible material with a density not less than 510 kg/m<sup>3</sup>.

\*\*\* Contact your flooring supplier for further information

\*\*\*\* Not suitable for the wood species beech and maple



Modern Home	Salsa	lacquer ultraloc 188 full length	lacquer ultraloc 188 half length	natura ultraloc 188 full length	lacquer combiloc 190 full length	natura combiloc 190 full length
-------------	-------	----------------------------------	----------------------------------	---------------------------------	----------------------------------	---------------------------------

### Salsa 14mm 3-strip

redoak		o			o	
oak select					x	
oak natur	o	o	o	o	o	o
oak nordic white					o	
oak white (robust)						o
oak rustical	x	x	x	x	x	x
oak nature brushed						o
oak basket weave *					o	
ash nature	o		o		o	o
ash white						o
ash cognac					o	o
ash cognac brushed						o
maple select (canadian)					x	
maple nature (canadian)	o		o		o	o
maple european		o			o	
birch					o	
birch honey					o	o
cherry	o		o		o	o
cherry robust		o				
beech nature	o	o	o		o	o
beech classic	x					
beech robust		o				
walnut					o	o
merbau	o	o	o		o	o
african mahogany					o	o
jatoba					o	o
doussié africana					o	o
doussié bipendensis					o	o

\* Cannot be installed together with other Salsa products

### Modern Home

Bravo

lacquer ultraloc natura ultraloc

### Bravo 14 3-strip 188 mm

oak	o	o
ash	o	o
maple	o	
birch	o	
cherry	o	
beech	o	

o = Class 0 Standard range with stock

x = Class 2 Falling products, Subject to availability

### Wood floors, Brinell Hardness (BHN), EN1534

