

**PRODUCT
DATA SHEET**

Tarkett Trend 200

Vinyl Collection

December 2014

Type of flooring

EN ISO 10582 Type 1 **Vinyl Floorcovering**

Class of use

EN ISO 10874



23



32



41

Class

Description



EN ISO 24346

(Previously EN 428)

2,00 mm



EN ISO 24340

(Previously EN 429)

0,40 mm



EN ISO 24341

(Previously EN 426)

25 m

4+3+2m



EN ISO 23997

(Previously EN 430)

2,150 kg/m²



EN 660-2

Abrasion resistance **≤2mm³**
(Class T according to EN 649)



ISO 4918

(EN 425)

Castor wheel test

OK



EN ISO 717/2

Impact sound absorption

ca. 13 dB



EN ISO 24343-1

(Previously EN 433)

Static indentation

≤ 0,10 mm

Other Characteristics



ISO 105/B02

Light fastness

≥ 6



Slip resistance

EN 13893

DIN 51130

μ ≥ 0,30

R10



Fire Classification

EN 13501-1

Cfl-s1

(glued over wooden panel)

Report N° : **RA14-0114**



EN ISO 23999

(Previously EN 434)

Dimensional stability

≤ 0,40 %



Recyclable

OK



EN ISO 10456

(EN 12524)

Thermal resistance
for underfloor heating

0,02 m²/kW



**Chemical
resistance**

OK



EN 1815

Static electrical
propensity

≤ 2 kV



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.