

**TEKNISK
DATABLAD**

AQUARELLE DESIGN GULV 3m

TopClean PUR-forsterket
Kolleksjon 2016 - 2017

September 2016

Gulvtype

EN 649

Vinylgulv

Bruksklasse

EN 685



23



32



41

Klasse



EN 428
Total tykkelse

2,00 mm



EN 429
Slitesjikt

0,40 mm



EN 426
Dimensjon

15 - 25 m
3m



EN 430
Total vekt

2,150 kg/m²



EN 660-2
Slitasjegruppe

T



EN 433
Inntrykks-
merker

≤ 0,10 mm

Annen informasjon



ISO 105/B02
Lysekthet

≥ 6



EN 13501-1
Brannklasse

Bfl-s1



EN 12524
Varmemotstand

0,02 m²/kW



EN 13893
DIN 51130
Sklihemming

≥ 0,30 μ
R9



EN 1815
Statisk oppladning

≤ 2 kV



EN 13553
Vanntetthet

Godkjent



Aquarelle Floor 3m

0131-0005-DoP-2013-07
www.tarkett.se

Made by: Tarkett GDLSA.
Lentzweiler - LUXEMBURG



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.