


HETEROGENEOUS  
ACOUSTIC VINYL

## Tapiflex Evolution

### Specification

Acoustic flexible vinyl floorcovering with a new foam backing on a non woven glass fiber stabilized carrier. This HE vinyl is reinforced with TopClean XP™. Product standard: EN 651.




CERTIFICATION & CLASSIFICATION STANDARDS		Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft	
Type of floorcovering	- EN 651	Heterogeneous acoustic vinyl			
CE Certification	EN 14041	Yes			
Impact sound reduction	EN ISO 140-8 EN ISO 717-2	ΔL <sub>w</sub> 17 dB			
Acoustical Improvement	NF S31-074	L <sub>w,eq</sub> < 65 dB			
Classification	ISO 10874 - EN 685	34			
TECHNICAL CHARACTERISTICS		STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Wear layer thickness	EN 429	1.00 mm	0.90 mm	0.70 mm	
Surface Treatment		TopClean XP™	TopClean XP™	TopClean XP™	
Total thickness	ISO 24346 - EN 428	3.35 mm	3.20 mm	3.05 mm	
Abrasion Group / mm³	EN 660-2	Group T : ≤ 2.0	Group T : ≤ 2.0	Group T : ≤ 2.0	
Total weight / g/m²	ISO 23997 - EN 430	3570	3440	3270	
Form of delivery	ISO 24344 - EN 426	Sheet (rolls)			approx. 23 running metres x 200 cm
TECHNICAL PERFORMANCES		STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Dimensional stability	EN 434	Length + width < 0.10%			
Reaction to fire	EN 13501-1	B, s1 on any A2 <sub>s</sub> or A1 <sub>s</sub> substrate C, s1 on any derivative wood substrate			
Static indentation	ISO 24343-1 - EN 433	0.08 mm			
Castor chair	ISO 4918 - EN 425	No damage			
Furniture leg	EN 424	No damage			
Curl resultant to heat	EN 434	≤ 8 mm			
Electrostatic properties	EN 1815 EN 1081 EN 14041	< 2 kV R1 > 10 <sup>9</sup> Ω Antistatic on concrete			
Hygiene	-	Does not contribute to infection spreading			
Chemical resistance	ISO 26987 - EN 423	High resistance			
Thermal resistance	EN 10456	0.04 m² K/W			
Underfloor heating		Suitable			
Light fastness	EN ISO 105-B02	≥ 6			
Slip resistance	DIN 51130 EN 13893	R9 μ ≥ 0.3			
Colours		12	9	Spaghetti XXL: 2 - Spaghetti: 8 Spice & Candy: 18, Havane: 5 - Uni: 4, Pastille: 2 - Draft: 6	

HETEROGENEOUS  
COMPACT VINYL

## Accent Evolution

### Specification


Compact flexible vinyl floorcovering. This HE vinyl is reinforced with TopClean XP™. Product standard: EN 649.




CERTIFICATION & CLASSIFICATION STANDARDS		Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft	
Type of floorcovering	ISO 10582 - EN 649	Heterogeneous compact vinyl			
CE Certification	EN 14041	Yes			
Classification	ISO 10874 - EN 685	34-43			
TECHNICAL CHARACTERISTICS		STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Wear layer thickness	EN 429	1.00 mm	0.90 mm	0.90 mm	
Surface Treatment		TopClean XP™	TopClean XP™	TopClean XP™	
Total thickness	ISO 24346 - EN 428	2.10 mm	2.00 mm	2.00 mm	
Abrasion Group / mm³	EN 660-2	Group T : ≤ 2.0	Group T : ≤ 2.0	Group T : ≤ 2.0	
Total weight / g/m²	ISO 23997 - EN 430	3100	2990	2990	
Form of delivery	ISO 24344 - EN 426	Sheet (rolls)			approx. 23 running metres x 200 cm
TECHNICAL PERFORMANCES		STANDARDS	Salt & Pepper	Sand	Spaghetti XXL, Spaghetti, Spice & Candy, Havane - Uni, Pastille - Draft
Dimensional stability	EN 434	Length + width < 0.10%			
Reaction to fire	EN 13501-1	B, s1 on any A2 <sub>s</sub> or A1 <sub>s</sub> substrate C, s1 on any derivative wood substrate			
Static indentation	ISO 24343-1 - EN 433	0.03 mm			
Castor chair	ISO 4918 - EN 425	No damage			
Furniture leg	EN 424	No damage			
Curl resultant to heat	EN 434	≤ 8 mm			
Electrostatic properties	EN 1815 EN 1081 EN 14041	< 2 kV R1 > 10 <sup>9</sup> Ω Antistatic on concrete			
Hygiene	-	Does not contribute to infection spreading			
Chemical resistance	ISO 26987 - EN 423	High resistance			
Thermal resistance	EN 10456	0.02 m² K/W			
Underfloor heating		Suitable			
Light fastness	EN ISO 105-B02	≥ 6			
Slip resistance	DIN 51130 EN 13893	R9 μ ≥ 0.3			
Colours		12	9	Spaghetti XXL: 2 - Spaghetti: 8 Spice & Candy: 18, Havane: 5 - Uni: 4, Pastille: 2 - Draft: 6	

The above information is subject to modification for the benefit of further improvement (06/12).

For more detailed technical information, please contact Tarkett. Please follow Tarkett's installation and maintenance instructions, included on the packaging, carefully.



According to European Classification  
ISO 10874 - EN 685  
TX Evolution



According to European Classification  
ISO 10874 - EN 685  
Accent Evolution



**WESTERN EUROPE:** Austria: Tarkett Holding GmbH, Niederlassung Wien – Tel. +43 1 47 88 062 Belgium: Tarkett France Belux – Tel. +32 16 35 98 80 Denmark: Tarkett A/S – Tel. +45 43 90 60 11 Finland: Tarkett Oy – Tel. +358 9 5406 5870 France: Tarkett SAS – Tel. +33 1 41 20 42 49 Germany: Tarkett Holding GmbH, Bereich Objekt – Tel. +49 62 33 810 Greece: Tarkett Monoprosopi Ltd – Tel. +30 210 6745 340 Italy: Tarkett S.p.A. – Tel. +39 0744 7551 Luxembourg: Tarkett GDL SA – Tel. +352 949 211 8804 Netherlands: Tarkett Holding GmbH, Vestiging Nederland – Tel. +31 76 57 80 760 Norway: Tarkett AS – Tel. +47 32 20 92 00 Portugal: Tarkett SA – Tel. +351 21 427 64 20 Spain: Tarkett Floors S.L. – Tel. +34 91 358 00 35 Sweden: Tarkett Sverige AB – Tel. +46 771 25 19 00 Switzerland: Tarkett Holding GmbH, Bereich Objekt Schweiz – Tel. +41 043 233 79 24 Turkey: Tarkett Aspen – Tel. +90 212 213 65 80 United Kingdom: Tarkett Ltd – Tel. +44 (0) 1622 854 040 **EASTERN EUROPE:** Baltic Countries: Tarkett Baltics: Tel. +370 37 262 220 Czech Republic: Tarkett France SAS, org. slozka – Tel. +420-271 001 602 Hungary: Tarkett France SAS – Tel. +36 1 437 8150 Poland: Tarkett Polska Sp. z o.o. – Tel. +48 22 639 31 68 Russian Federation: ZAO Tarkett RUS – Tel. +7 495 775 3737 Slovakia: Tarkett France SAS, org.zlozka – Tel. +421 248 291 317 South East Europe: Tarkett Trade d.o.o. – Tel. +381 21 7557 649 (44) 569 12 21 Ukraine: Tarkett UA – Tel. +38 (0) 44 569 12 21 **ASIA AND OCEANIA:** Australia: Tarkett Australia Pty Ltd – Tel. +61 2 88 53 12 00 China: Tarkett Floor Covering (Shanghai) Co. Ltd. – Tel. +86 (21) 60 95 68 38 ext 841 Hong Kong: Tarkett Asia Pacific Ltd. – Tel. +852 2511 8716 India: Tarkett France (India Branch) – Tel. +91 11 4352 4073 South East Asia: Tarkett Asia Pacific Ltd – Tel. +65 97 57 36 45 **AFRICA:** Tarkett International: Tel. +33 1 41 20 41 01 **MIDDLE EAST:** Tarkett Middle East: Tel. +961 1 51 3363/4 Israël: Tarkett International: Tel. +33 1 41 20 41 01 **NORTH AMERICA:** USA: Tarkett Inc. – Tel. +1 713 869 5811 / Johnsonite – Tel. +1 440 543 8916 Canada: Tarkett Inc. – Tel. +1 450 293 173 **LATIN AMERICA:** Brazil: Tarkett Fadamac – Tel. 55 12 3954 7108 Other countries: Tarkett America Latina – Tel. +55 11 3047 7200 Argentina - Chile - Uruguay: Tarkett Latam Mercosur – Tel. 54 11 48 06 74 28 / 54 9 11 44 46 88 82 Colombia - Panama - Caribbean: Tarkett Latam Andina - Tel. 57 1 759 5781 / 57 312 273 1566 Bolivia - Ecuador - Paraguay - Peru: Tarkett Latam Sur Oeste - Tel. 55 11 3047 7233 Mexico/Central America: Tarkett Latam Mexico - Tel. 52 735 35 63 918 / 52 55 51 07 9524