

**PRODUCT  
DATA SHEET**

# STARFLOOR CLICK 50 Planks

November 2012

**Type of flooring**

**EN 649**

**Compact Resilient Flooring**

**Class of use**

**EN 685**



**23**



**32**

**Class**

## Description



**EN 428**

**5,00 mm**



**EN 429**

**0,50 mm**



**EN 660-2**

Abrasion group

**T  
≤ 2,00 mm<sup>3</sup>**



**EN 430**

**9,2 kg/m<sup>2</sup>**



**EN 427**

Length + Width

**122 cm**

**20 cm**



**EN 425**

Castor chair  
Fully adhered

**OK**



**EN ISO 717/2**

Impact sound  
absorption

**5 dB**



**EN 433**

Static  
indentation

**≤ 0,08 mm**

## Optional Characteristics



**ISO 105/B02**

Light fastness

**≥ 6**



**EN 1815**

Static electrical  
propensity

**≤ 2 kV**



**Fire Classification**

EN 13501-1

**Bfl-s1**

Report N° :



**EN 434**

Dimensional  
stability

**≤ 2 mm**

**< 0,10 %**



**Recyclable**

**OK**



**EN 12524**

Thermal resistance

**0,04 m<sup>2</sup> k/W**



**Slip resistance**

DIN 51130

En 13893

**R10  
μ≥0,30**



EN 14041 : 2004

Manufactured in PRC by  
**TARKETT**

STARFLOOR  
CLICK 50

TARKETT  
BALANCED  
CHOICE

**82 %**

Natural

**100 %**

Recyclable



\*TVOC AT 28 DAYS