

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

No 211001

Unique identification code of the product-type: **MasterSeal Roof 2110**

Intended use/es:

EN 1504-2
Concrete protection and repair products

Manufacturer: **Master Builders Solutions Deutschland GmbH**
Donnerschweer Str. 372
D-26123 Oldenburg

System/s of AVCP:

EN 1504-2: System 4 (for uses with low performance requirements in buildings and civil engineering works)

Harmonised standard: **EN 1504-2:2004**

Notified body/ies:

KIWA Polymer Institut
D-65439 Flörsheim-Wicker
(CE identification number: 1119)

Declared performance/s: **EN 1504-2:**

The product is used in surface protection system:

MasterSeal Roof 2110

consisting of components:

MasterTop P 617, MasterSeal P 681, P 682, P 684 or P 698 (depending on substrate)
MasterSeal M 800
MasterSeal TC 259

Table 1: Performance in system

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Linear shrinkage	NPD	System 4	EN 1504-2:2004
Compressive strength	NPD		
Coefficient of thermal expansion	NPD		
Abrasion resistance	NPD		
Cross cut	NPD		
Permeability to CO ₂	s _D > 50 m		
Water vapour permeability	class I		
Capillary absorption and permeability to water	w < 0,01 kg/m ² x h ^{0,5}		
Thermal compatibility	> 3 MPa		
Resistance to thermal shock	NPD		
Chemical resistance	NPD		
Resistance to severe chemical attack	reduction in hardness < 50 %		
Crack bridging ability	Static: A5 (23 °C) Dynamic: B4.2 (23 °C)		
Impact resistance	Class III		
Adhesion strength by pull off test	≥ 1,5 N/mm ²		
Reaction to fire	Efl*		
Skid resistance	NPD		
Artificial aging	NPD		
Antistatic behaviour	NPD		
Adhesion on wet concrete	NPD		
Release of dangerous substances	NPD		

Appropriate Technical Documentation and/or Specific Technical Documentation:

*=Performance without further testing: Reaction to fire: Efl

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Klaus Claassen
Product Manager Waterproofing Resins Europe

Oldenburg, 04.01.2021

Annex:

Technical data sheets for use in buildings (system build-ups according to respective technical data sheets)