

DECLARATION OF PERFORMANCE

DE0246/05

04.01.2021

Unique identification code of the product-type:

MasterInject 1360 (DE0246/05)

Intended use/es:

EN 1504-5 Methods 1.5/4.5/4.6

U(F1) W(2) (1) (15/35) (0)

U(F1) W(5) (1/2) (15/35) (0)

Concrete injection product

Manufacturer:

Master Builders Solutions Deutschland GmbH, Donnerschweer Str. 372, D-26123 Oldenburg

System/s of AVCP:

System 2+

Harmonised standard / Notified body/ies:

EN 1504-5:2004

**Gesellschaft für Materialforschung und Prüfungsanstalt für das Bauwesen Leipzig mbH -
MFPA Leipzig GmbH (NB 0800)**

Declared performance/s:

| Essential characteristics | Performance | System of assessment and verification of constancy of performance | Harmonised technical specification |
|-----------------------------------|---|---|------------------------------------|
| Adhesion by tensile bond strength | Cohesive failure in the substrate | System 2+ | EN 1504-5:2004 |
| Adhesion by slant shear strength | NPD | | |
| Shrinkage | NPD | | |
| Glass transition temperature | > 40 °C | | |
| Workability | Crack width 0,2 mm dry Crack width 0,5 mm damp | | |
| Chloride content | NPD | | |
| Durability | Cohesive failure in the substrate | | |
| Corrosion behavior | Deemed to have no corrosive effect. | | |
| Dangerous substances | Comply with 5.4 (EN 1504-5) | | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



.....
Jürgen Baumann



.....
Volker Schwarz