GROUT SEALANT

Self-declaration that the named products comply with the requirements for sealant as per BREEAM-NOR's chapter HEA 9

This form must be filled out by the MANUFACTURER of sealant.

It is important that the information given here is correct, and we strongly encourage thoroughness in researching the extent to which emission testing and/or test reports show that the product complies with the standards and emission limit values required by BREEAM-NOR. If in doubt, the manufacturer should consult own internal and external experts. **Incorrect and misleading information can have legal consequences.**

Once filled-out, the form must be signed by a <u>legally responsible person</u> from the manufacturer, e.g. a technical manager or a managing director.

MANUFACTURER:		Dana Lim A/S					
PRODUCT TRADE Montage Ekstra NAME:		292					
DOCUMENTATION				YES	NO	Comments	
REQUIREMENTS			Relevant standards				
1.	The product has been tested to document that its TVOC emission is below 0,2 mg/m ² h ^{1) 2)}		NS-EN 15251:2007 (Appendix C)	×		M1	
2.	The product has been tested to document that its formaldehyde emission is below 0,05 mg/m²h¹¹ 2)		NS-EN 15251:2007 (Appendix C)	x		M1	
3.a	The product has been tested to document that ammonia emission is below 0,03 mg/m²h¹) 2)3)		NS-EN 15251:2007 (Appendix C)	x		M1	
3.b	An emission test measuring the am not available, but the undersigned 1) That ammonia is not trace product, AND 2) The product does not con can decompose to ammonia		can confirm ably active in the cain chemicals that				
4.	The product has been tested to document that its emissions of cancer-causing compounds (IARC)		NS-EN 15251:2007 (Appendix C)	х		M1	

The form is developed by NCC in cooperation with Skanska and NGBC. It is freely distributed via NGBC and Chemxchange. Users of the form are solely responsible for ensuring that the version and contents of the form are correct. NCC, Skanska, NGBC or Chemxchange cannot be held responsible for possible errors. Filled-out forms are not an official approval from NGBC or others.

	are below 0,005 mg/m ² h ^{1) 2)}			
5.	The product has been tested to document that odour dissatisfaction is below 15%. Apllies only if it is relevant for the product. ¹⁾	NS-EN 15251:2007 (Appendix C)	x	M1
6.	The tests in 1-5 have been performed acc. to the ISO 16000-series with measurements made after 28 days.	ISO 16000	X	M1

- When assessing different types of emission certificates against the requirements in NS-EN 15251, you can find help on http://www.breeam.org/page.jsp?id=27.
- Please note that the emissions here are measured in mg/m²h. Most emission certificates use the unit mg/m³. It is possible to convert these units in order to compare the results. A laboratory of your choice can assist you.
- Note that M1 is the only known emission mark classification which includes measurement of ammonia emissions.

Legally responsible: Dorthe Christensen	Position: HSE-manager	Date: 08.01.2014
Signature:		