




# X-FS Form Stop

## Product data

### Dimensions



### General information

#### Material specifications

Nail: zinc coating: 5–20 µm


#### Recommended fastening tools

DX 460, DX 36, DX 460-MX



See **X-FS fastener program** in the next pages and **Tools and equipment** chapter for more details.

## Applications

### Examples



Positioning concrete forms on concrete surfaces. Leave in place, grey polyethylene is non rusting, nearly invisible and non-conductive.



X-FS is suitable and usable for minor forming applications




## Load data

### Recommended working loads

$V_{rec} = 400 \text{ N}$

(predominantly static, however, vibration from concrete compacting is allowed)



## Application requirements

### Thickness of base material

Concrete:  $h_{min} = 80 \text{ mm}$

### Spacing and edge distances

Spacing and edge distances depending on job site requirements.

### Corrosion information

For temporary fixations no restrictions exist.

## Fastener program

Fastener				Tools
Designation	Item no.	$L_s$ [mm]	Nail shank diameter [mm]	Designation
① X-FS C 52 *	407346	52	3.5	DX 460, DX 36
② X-FS MX **	408022			DX 460-MX

\* For unusual applications, X-FS available with other nails on special order

\*\* X-FS without nail for fastening with collated nails.

## Cartridge selection and tool energy setting

<b>Cartridge recommendation:</b>	Steel:	<b>6.8/11M red</b> cartridge
	Concrete:	<b>6.8/11M yellow</b> or <b>red</b> cartridge
	Masonry:	<b>6.8/11M yellow</b> or <b>green</b> cartridge

Tool energy adjustment by setting tests on site.