

**TECHNICAL DATA****TYPICAL APPLICATIONS**

- > Easy tear
- > Flexible
- > Adequate to uneven shapes

**CONSTRUCTION**

Overall Grade: Inside/Outside  
 Backing: PVC  
 Adhesive: Pressure -sensitive adhesive

**COLOR(S)**

 blue  black  red  green/yellow

**STANDARD SIZE**

Width(s): 19mm  
 Length(s): 10m, 3m

Contact your BDT sales representative for other available sizes.

**PHYSICAL PROPERTIES**

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	124	um	-
Initial Adhesion	4,54	N/25mm	-
Breakdown Voltage	4	KV	-
Holding Power	>60	min	
Service Temperature Range	from 0 to +80	° C	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.