




Novilux traffic textile, traffic rock and traffic wood meet the requirements of ISO 26986 / EN 653

	Total thickness	ISO 24346 / EN 428	3.0 mm
	Thickness wearlayer	ISO 24340 / EN 429	0.70 mm
	Collection size		17
	Domestic heavy	ISO 10874 / EN 685	Class 23
	Commercial heavy	ISO 10874 / EN 685	Class 33
	Light industrial general	ISO 10874 / EN 685	Class 42
	Roll width	ISO 24341 / EN 426	400/200 cm
	Roll length	ISO 24341 / EN 426	25 m
	Total weight	ISO 23997 / EN 430	2.8 Kg/m ²
	Dimension stability	ISO 23999 / EN 434	≤ 0.10%
	Residual indentation	ISO 24343-1 / EN 433	≤ 0.15 mm
	Abrasion resistance	EN 660 Group T	Excellent
	Acoustical impact noise reduction	EN ISO 140-8 / EN ISO 717-2	17 dB
	Castor chair continuous use	ISO 4918 / EN 425	Superior
	Light fastness	ISO 105-B02	Blue scale 6/7
	Resistance to chemicals	ISO 26787 / EN 423	Very good
	Slip resistance	DIN 51130	R10
	Heat insulation	DIN EN 12664	0.03 m ² K/W
	Heat dissipation	DIN 52614	W1:35 / W10:200

Novilux traffic textile, traffic rock and traffic wood meet the requirements of EN 14041

CE

	Reaction to fire	EN 13501-1	B _{fl} S1
	Slip resistance	EN 13893	DS-μ ≥ 0,30
	Statische electriciteit	EN 1815	≤ 2 kV
	Thermal conductivity	EN 12524	0.25 W/m ² K



DIAMOND SEAL XS NOVICLEAN AQUAGRIP LDF 4m BROAD DESIGN NOVIGROUT RAPID LAY



Forbo Flooring Systems is part of the Forbo Group, a global leader in flooring, bonding and movement systems and offers a full range of flooring products for both commercial and residential markets. High quality linoleum, vinyl, textile, flocked and entrance flooring products combine functionality, colour and design, offering total flooring solutions for any environment.

The management system of Forbo-Novilon B.V., Coevorden the Netherlands is certified in accordance with ISO 9001 and ISO 14001.