


















# Teknisk informasjon

Flotex oppfyller kravene i EN 1307

		Banevare	Flis
	Total tykkelse	ISO 1765 4.3 mm	5.3 mm
	Offentlig - kraftig	EN 685 Klasse 33	Klasse 33
	Rullbredde	2.0 m	-
	Rullengde	30 m	-
	Dimensjoner flis	-	50 x 50 cm
	Forpakning flis	-	12 (3m <sup>2</sup> )
	Total vekt	ISO 8543 1.8 kg/m <sup>2</sup>	4.5 kg/m <sup>2</sup>
	Dimensjonsstabilitet	ISO 2551 / EN 986 < 0.2 %	< 0.2 %
	Slitasjestyrke	EN 1307 annex F >1000 omdreininger	>1000 omdreininger
	Rullende stolhjul	EN 985 r = ≥ 2.4 kontinuerlig belastning	r = ≥ 2.4 kontinuerlig belastning
	Lysbestandighet	EN-ISO 105-B02 ≥ 6	≥ 6
	Sklihemmende egenskaper	UK SRG pendulum Tørr - meget gode sklihemmende egenskaper Våt - gode sklihemmende egenskaper	Tørr - meget gode sklihemmende egenskaper Våt - gode sklihemmende egenskaper
	Akustikk	EN-ISO 717-2 Trinnlydsforbedring Δlw = 20 dB	Trinnlydsforbedring Δlw = 19 dB
		ISO 354 Lydabsorpsjon = 0.10	Lydabsorpsjon = 0.10
	Vannnett	EN 1307 annex G Godkjent	Godkjent
	Flotex oppfyller kravene i EN 14041	EN 14041 <b>CE</b> 1200101-DoP-306	EN 14041 <b>CE</b> 1200201-DoP-306
	Brannegenskaper	EN 13501 B <sub>s</sub> -s1	B <sub>s</sub> -s1
	Sklihemmende egenskaper	EN 13893 DS: ≥ 0.30	DS: ≥ 0.30
	Generering av kroppsspenning	ISO 6356 < 2 kV	< 2 kV
	Varmeledningsevne	ISO 8302 0.048 m <sup>2</sup> K/W	0.040 m <sup>2</sup> K/W

**Norway**  
 Forbo Flooring AS  
 Hagaløkkveien 7  
 1383 Asker  
 Tlf: 66 77 12 00  
 Fax: 66 77 12 40  
 E-Mail: info.norway@forbo.com  
 www.forbo-flooring.no