




SPECIFICATIONS LUMENS Li-Po 2800 mAh SPECIFICATIONS 184 g 10° - 70°



UNIQUE SELLING POINTS (USP)

HIGH CAPACITY LI-PO

The battery inside the V3prorechargeable is a high capacity low weight Li-Po cell with 2800 mAh. The battery is charged directly in the battery, and therefore you will be able to charge the battery while using a spare battery (sold separately).


SLIDING HYPERFOCUS™

The sliding Hyperfocus™ optical system collects the LED radiance and distributes it with maximum efficiency from a perfect round floodlight beam to a highly intensive, long range spot beam. Just slide the head of the lamp for the correct light setting.

RED WARNING LIGHT

The red blinking warning light on the back of the batterypack will make you visible from behind. The light can be turned on and off.

LIGHT CURVE AND RUNTIMES





SPECIFICATIONS

LED / Focus configuration:	1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Treatment:	Hi-Tech Plastic Compound / Aluminium
Case Color:	Black / Anthracite Dark Grey
Switch:	Metal Switch Below Head - Max, Dimmer with Memory and Transportation lock
Headband:	Split with silicone stripes, Fits to 50-70 centimeters
Weight incl. battery:	184g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperature:	-20°C to +35°C

ELECTRONICS

Built in Controller:	Yes, 3-step controller by press
Standard Power Source:	Li-Polymer (2800 mAh)
Beam / Distance:	Variable from Spot to Floodlight / 245 Meters
Luminous Flux:	Max: 750 lm / Standard 180 lm / Dimming: 6-300 lm
Lighting Time:	Max: 3h / Standard: 8h / Low Dim: 225h
Accessories included:	Removable cable, Washable Head- band, USB Charging Cable
Charging temperature:	0°C - +45°C

PACKAGING

Customs Tariff Number:	8513 1000
Packaging:	Presentation tube
Single Box Content / Size / Weight:	1 pcs, height/diameter, 18 x 9,7 cm / 409 g
Master Box Content / Size / Weight:	32 pcs, 40 x 40 x 40 cm / 13.8 kg
Order's Address:	info@suprabeam.com
Part No.:	612.5205
EAN-CODE:	5704049907553

FEATURES



DC CONVERTER TECHNOLOGY

Highly efficient electronic circuitry. That reduces heat development of the Power LED and decreases the energy consumption.



ELECTRONIC DIMMING

Our eletronic dimming lets you dim the light to the



desired level with ease



VERSATILE PLUG SYSTEM

The versatile plug system lets you change, rearrange and repair your headlamp



COOLING CORE

The high strength aluminium cooperates with the "heatsink" to cool off the LED



ADJUSTABLE ANGLE

Adjust the angle of your headlamp for all kinds of situations



Lets you lock the buttons on $% \left\{ 1,2,\ldots ,n\right\}$ your headlamp for transportation



WATER RESISTENT - IPX4

This IP-rating indicates

that your product is water

resistant

SLIDING FOCUS

Focus from wide floodlight to spotlight with a simple slide of the lamp head



TRANSPORTATION LOCK



WARNING LIGHT

The red warning light will make you visible from behind. The light can be turned on and off



RESERVE LIGHT

Gives you visual notification, that the battery is low and gives you time to head home



RECHARGEABLE

Rechargeable products will prevent you from using and throwing away alkaline batteries



USB CHARGER

All of our rechargeable products are compatible with USB. This enables you to charge everywhere