



DECLARATION OF PERFORMANCE
in accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)
amended by Commission Delegated Regulation (EU) No 574/2014

for the product **ARDEX SE**
No 73031

1. Unique identification code of the product type: **F-INT-CC 20HM**
XS 1
PW-INT-CC 20HM
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for joints for facades, sanitary areas and pedestrian walkways

3. Name, registered trade name or registered trade mark and contact address of the manufacturer:

ARDEX GmbH
Friedrich-Ebert-Str. 45
58453 Witten
Germany

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) of the Regulation (EU) no 305/2011:

not relevant

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
System 3 for reaction to fire

- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body **MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW)** with the identification number **0432** performed the test according to EN 15651:2012-12, Part 1, 3 and 4.

The notified body **MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN (MPA NRW)** with the identification number **0432** performed the reaction to fire.

6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment was issued:

Not relevant

7. Declared Performance:


8.

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire:	E	EN 15651-1: 2012 EN 15651-3: 2012 EN 15651-4: 2012
Release of chemicals dangerous to health and the environment:	evaluated	
Resistance to flow:	≤ 3 mm	
Loss of volume:	≤ 10 %	
Tensile properties at maintained extension after water immersion:	passed (NF)	
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30 °C):	passed (NF)	
Tensile properties at maintained extension:	passed (NF)	
Microbiological growth:	0	
Tear resistance:	passed (NF)	
Tensile properties - secant modulus at -30°C for cold climate areas:	≤ 0.9 MPa	
Durability:	passed (NF)	


9.

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Dr. Jörg W. Sieksmeier
R & D Director

ARDEX GmbH
Friedrich-Ebert-Str. 45
58453 Witten


Ann-Kristin Quintern
R & D Section Head

Witten, 11th January 2021

(Place and date of issue)