

VERSION: 1.0 In acc. with the requirements of BREEAM-NOR 2016 version 1.1 (02.05.17)

WOOD FLOORING AND PARQUET

Self-declaration that the named products comply with the requirements for wood flooring and parquet as per BREEAM-NOR's chapter HEA 02

This form must be filled out by the MANUFACTURER of wood flooring and parquet acc. to EN 14342:2013

Approved emission certificates are M1¹ and EC 1².

If the product has one of the approved emission certificates, it is not necessary to fill in this form. Connect the emission certificate to the product in goBIM.

It is important that the information given here is correct, and we strongly encourage thoroughness in researching the extent to which emission testing and/or test reports show that the product complies with the standards and emission limit values required by BREEAM-NOR 2016. If in doubt, the manufacturer should consult own internal and external experts. Providing incorrect and misleading information can have legal consequences. Once filled-out, the form must be signed by a legally responsible person for the manufacturer, such as a technical director or a managing director.

MANUFACTURER: PRODUCT TRADE NAME:

PRODUCT ID:

Reinlein Holz & Parkett Ges.m.b.H. A-4651 Stadl-Paura, Wimsbacher Str. 21

STRILINE

INDUSTRIAL PARQUET

The following is hereby confirmed by the manufacturer:

- 1. The product is in accordance with product standard: EN 14342:2013
- 2. The product has undergone an emission test³ which shows that its emissions are below the values⁴ shown in table 15 «Floor/Ceiling».

¹ Approved performance standard NS-EN 15251:2007, Appendix C

² Approved performance standard GEV Emicode



VERSION: 1.0 In acc. with the requirements of BREEAM-NOR 2016 version 1.1 (02.05.17)

Table 15: Emission limits for all product categories - Conversion table

| Ref | Wall | | Floor/ceiling | | Sealants | |
|------------------|--------|--------|---------------|--------|----------|--------|
| | µg/m²n | µg/m³h | µg/m²h | pg/m³h | µg/m²n | µg/m³h |
| TVOC 28d | 200 | 417 | 200 | 160 | 4260 | 60 |
| Formaldehyde 3d | 24 | 50 | 62,5 | 50 | 3550 | 50 |
| Formaldehyde 28d | 50 | 104 | 50 | 40 | 710 | 10 |
| Carcinogenic | 5 | 10 | 5 | 4 | 71 | 1 |

³Documentation (test in acc. with approved standard) can be requested if required.

A-4651 STADL-PAURA

3. The emission test has been performed in accordance with the following approved standards ISO 16000-9 together with ISO 16000-6 (volatile organic compounds), ISO 16000-3 (formaldehyde). Test and calculation shall be carried out according to EN 16516.

| Legally responsible: | Position: | Date: | |
|----------------------|---------------|------------|--|
| Hr. Peter Eisenkolb | office worker | 18.05.2020 | |

Signature:

This form is developed by SKANSKA NORGE AS, VEIDEKKE ENTREPRENØR AS, NCC NORGE AS and AS BACKE. It is freely distributed via ProductXchange. Users of the form are solely responsible for ensuring that the version and contents of the form are correct. SKANSKA NORGE AS, VEIDEKKE ENTREPRENØR AS, NCC NORGE AS, AS BACKE or coBuilder AS cannot be held responsible for any possible errors. Filled-out forms are not an official approval from SKANSKA NORGE AS, VEIDEKKE ENTREPRENØR AS, NCC NORGE AS, AS BACKE or coBuilder AS.

⁴Show accordance with units μg/m³ or μg/m²h