



Declaration of performances



N° WD-CPR-400/22/6-15

According to Article 4, 6 and ANNEX III of REGULATION (EU) No 305/2011
OF THE EUROPEAN PARLAMENT AND OF THE COUNCIL

1. *Unique identification of product-type*

Multi-layer parquet flooring

2. *Type, batch or serial number or any other element allowing identification of the construction product*

Type: **3-layer/ 3 -ply based parquet**, with different wood species in the top layer.

Commercial name: **WOODLINE PARQUETRY**

Total thickness: **22 mm**,

Width: **190/240/290/400mm**,

Length: **1820/2130/2450/3000 mm**

Top layer: Surface layer of single strip, two or three strips **hardwood species** – Oak, Beech, Ash, Maple, Walnut, Merbau, Kempas, Jatoba, Hevea and others – thickness **(6,0 ±0,1) mm**

Middle layer: **Wood elements** thickness **(14 ±0,1) mm**

Under layer: **Veneer** thickness **(2 ±0,1) mm**

Surface treatment: **Acrylic lacquer Miraphen® UV – Top Coat; Oil Miraphen® UV – Top Coat Oil**

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer*

Product intended for internal use as flooring in dry conditions with reaction to fire Class D_n-s1 for multilayer with surface coating and not specified above, minimum mean density 500 kg/m³, minimum overall thickness 14 mm with or without air gap underneath. In construction work are installed coated, varnished or oil-paint., in accordance with instruction of manufacturer.

4. *Name and contact details Manufacturer*

**FORESTRY TIMBER EXPORT SDN BHD (162992-W)
Level 8, Wisma General Lumber, Block D,
Peremba Square, Saujana Resort, 40150 Shah Alam, Malaysia**

5. *Name and contact address of authorized representative*

**Ján Antošík - DREVAN
prev. Bystrická 223
966 81 Žarnovica, Slovakia**

6. *System or systems of assessment and verification of constancy of performance of the construction product*

4

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard*

Accredited laboratory Notified Body No. 1478 LIGNOTESTING, a.s., Technická 5, 821 04 Bratislava, Slovak Republic has tested the products at the request of FORESTRY, TIMBER EXPORT SDN BHD, Level 8, Wisma General Lumber Block D, Peremba Square, Saujana Resort, 40150 Shah Alam, Malaysia by EN 14342:2005 + A1:2008 "Wood flooring. Characteristics, evaluation of conformity and marking"

performed:

for Customers' **Ing. Jozef Koňarik, A. Štefanku 1372/10
965 01 Žiar nad Hronom**

under system:

4

and issued:

**- Summary No. Z-20/030/13/3101/S1, 30 August 2013, Notified Body No.1478
- Summary No. Z-20/030/13/3101/S2, 30 August 2013, Notified Body No.1478
- Test report No. 800/20/0062/13, 30 August 2013, Notified Body No.1478
- Test report No. 800/20/0063/13, 30 August 2013, Notified Body No.1478
- Test report No. 277166, 31 August 2007, EPH Entwicklungs- und Prüflabor Holztechnologie GmbH,
Zellescher Weg 24, D-01217 Dresden, Germany**

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued*

9.	Declared performances		
	Essential characteristics ¹⁾	Performance ²⁾	Harmonised technical specification ³⁾
	Thickness	22,0 mm	EN14342: 2013
	Width	180 to 400 mm	
	Length	1820 to 3000 mm	
	Mass density	> 650 kg/m³	
	Reaction to fire	≥ C_{FI} - s1	
	Emission of formaldehyde	Parquet lacquered E1 Parquet oiled E1	
	Content of pentachlorophenol	≤ 5 ppm	
	Breaking strength	NPD	
	Slip resistance	NPD	
	Thermal conductivity	0,16 W/(m.K)	
	Biological durability	Class 1	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Gurjeet Singh - CEO
Kuala Lumpur – 1st January 2015



- 1) Column 1 shall contain the list of essential characteristics as determined in the harmonised technical specifications for the intended use or uses indicated in point 3 above;
- 2) For each essential characteristic listed in column 1 and in compliance with the requirements of Article 6, column 2 shall contain the declared performance, expressed by level or class, or in a description, related to the corresponding essential characteristics. The letters 'NPD' (No Performance Determined) shall be indicated where no performance is declared;
- 3) For each essential characteristic listed in column 1, column 3 shall contain:
- a) dated reference of the corresponding harmonised standard and, where relevant, the reference number of the Specific or Appropriate Technical Documentation used