

HALFHARD FLOORING, TEXTILE AND LAMINATE FLOORING

This form must be filled out by the manufacturer of flooring. If the manufacturer does not supply directly but through an intermediary (retailer, subcontractor, etc.) this intermediary has to pass on the form to the producer. Completed form should be included as part of the offer. It is important that the information given here is correct, and it encouraged thoroughness when investigating whether the emission tests and other certificates meet the standards and emission limits BREEAM NOR sets. If in doubt you should use the manufacturer's own internal experts and laboratories and other agencies providing testing and certifications for this.

Products defined as resilient floor coverings, textile and laminate are:

- Vinyl
- Linoleum
- Carpet
- Laminate flooring

The completed form must be signed by a legally responsible person at the manufacturer

MANUFACTURER: Polyflor Ltd, Manchester, UK

PRODUCTNAME: Enhanced Slip Resistant Sheet Vinyl Flooring EN 13845

Polysafe Standard

Polysafe Mosaic

Polysafe Astral

Polysafe Corona

Polysafe Hydro / Hydro Evolve

Polysafe Strata

Polysafe Ultima

Polysafe Vogue Ultra

Polysafe Verona

Polysafe Apex

Polysafe Quattro

Polysafe QuickLay

DOKUMENTATION			Yes, attached	No	Under preparation, completion (date)
REQUIREMENTS		Relevant standards			
1.	The product can be classified as E1 acc. test method EN 717-1:2004	EN 14041:2004	✓		Formaldehyde is not added to our products



Material Declaration

The product has an emission test which shows	NS-EN 15251:2007 (attachment C)		Yes, according to ISO
is below 0.2 mg/m2h ¹⁾		•	16000 series, AgBB (2012)
The product has an emission test which shows that the emissions of formaldehyde is less than 0.05 mg/m2h ¹⁾	NS-EN 15251:2007 (attachment C)	✓	Yes, Meets the limits as set by the AgBB Scheme (2012)
The product has an emission test which shows that emissions of ammonia is less than 0.03 mg/m2h ¹⁾²⁾	NS-EN 15251:2007 (attachment C)	✓	Yes, Meets the limits as set by the AgBB Scheme (2012)
The product has an emission test which shows that emissions of carcinogenic compounds (IARC) is less than 0,005 mg/m2h ¹⁾	NS-EN 15251:2007 (attachment C)	✓ 	Yes, Meets the limits as set by the AgBB Scheme (2012)
The product has a emission test that shows that dissatisfaction with the odor is below 15%	NS-EN 15251:2007 (attachment C)	√	Yes, see attached
The tests in paragraphs 2-6 are performed acc. ISO 16000 series with measurements done after 28 days	ISO 16000	✓	Yes, according to ISO 16000 series and AgBB Scheme
Production of the product has been certified according to ISO 14001 (or other third party certified environmental management system)		✓	Yes, all of our products are made within ISO 14001 approved factories
The product has an EPD (Environmental Product Declaration) prepared in accordance with ISO 14025 or EN 15804		✓	Yes, the products have an ERFMI Generic EN 15804 EPD. Please see attached and also please see bau- umwelt.de
	emission test which shows that the emissions of TVOC is below 0.2 mg/m2h¹) The product has an emission test which shows that the emissions of formaldehyde is less than 0.05 mg/m2h¹) The product has an emission test which shows that emissions of ammonia is less than 0.03 mg/m2h¹) The product has an emission test which shows that emissions of carcinogenic compounds (IARC) is less than 0,005 mg/m2h¹) The product has a emission test that shows that dissatisfaction with the odor is below 15% The tests in paragraphs 2-6 are performed acc. ISO 16000 series with measurements done after 28 days Production of the product has according to ISO 14001 (or o certified environmental mana) The product has an EPD (En Declaration) prepared in according to ISO 14001 (product) prepared in	emission test which shows that the emissions of TVOC is below 0.2 mg/m2h¹) The product has an emission test which shows that the emissions of formaldehyde is less than 0.05 mg/m2h¹) The product has an emission test which shows that emissions of ammonia is less than 0.03 mg/m2h¹) The product has an emission test which shows that emissions of carcinogenic compounds (IARC) is less than 0,005 mg/m2h¹) The product has a emission test that shows that dissatisfaction with the odor is below 15% The tests in paragraphs 2-6 are performed acc. ISO 16000 series with measurements done after 28 days Production of the product has been certified according to ISO 14001 (or other third party certified environmental management system) The product has an EPD (Environmental Product Declaration) prepared in accordance with ISO	emission test which shows that the emissions of TVOC is below 0.2 mg/m2h¹) The product has an emission test which shows that the emissions of formaldehyde is less than 0.05 mg/m2h¹) The product has an emission test which shows that emissions of ammonia is less than 0.03 mg/m2h¹) The product has an emission test which shows that emissions of ammonia is less than 0.03 mg/m2h¹) The product has an emission of carcinogenic compounds (IARC) is less than 0,005 mg/m2h¹) The product has a emission test that shows that dissatisfaction with the odor is below 15% The tests in paragraphs 2-6 are performed acc. ISO 16000 series with measurements done after 28 days Production of the product has been certified according to ISO 14001 (or other third party certified environmental management system) The product has an EPD (Environmental Product Declaration) prepared in accordance with ISO

¹⁾ Note that the issues here are given in mg/m2h. Most states emission certificates issued in mg/m3. These are, in other words not immediately comparable. There are methods to convert these so that we can compare the results. Your laboratory can help you with this.

²⁾ Note that M1 is the only emission labeling system where ammonia is included as one of the issues being measured.





Check the left column if the following statements is correct for the product				
	The product does not have a emission test that measures the emissions of ammonia, but undersigned can confirm			
	That ammonia is not traceable active in the product AND The product does not contain substances that may cleave to ammonia			
✓	Undersigned can confirm that the product is not added any materials containing formaldehyde during production or preparation after production. These can be classified as E1 without testing, See ISO 13986:2004 for detailed information.			
✓	Undersigned can confirm the absence of regulated impregnating agents and that minimum requirements are met. (see EN 13986:2004 for details)			
✓	Undersigned can confirm that the product does not contains substances which are BREEAM NOR checklist A20. The same checklist defines what valid evidence is.			

Mike Minett	M.G.Minett	Quality Manager	6th February 2019
Signature		Position	Date