

2018

15mm and 14mm

KARELIA MULTI-LAYER PRODUCT DATA SHEET NATURE OIL

PRODUCT DESCRIPTION

15 mm and 14mm parquet flooring (floating/glued down) – manufactured according to EN 13489

TECHNICAL PROPERTIES

Length 2423/2421/2266/2100/2000/1900/1860mm

Width 200/198,5/188/187/150/148/138mm

Thickness approx. 15mm and 14mm

Hardwood surface thickness approx. 3,5 mm ($\pm 0,5$ mm)

Middle layer thickness approx. 9mm/10mm (pine/spruce)

Bottom layer thickness approx. 1,8 mm (spruce veneer)

Deviation of squareness max. 0,2 mm

Locking system Profiloc Licensed to Välinge's patent family 2G or 5G-system

Height difference max. 0,2 mm

Moisture during first delivery $7,5 \pm 1$ %

Height difference (lipping) max. 0,2 mm

SURFACE LAYER COATING SYSTEM – NATURE OIL

BONDING

E1-classified amino resin (EN 717-1)

PACKAGING AND MARKING (EN 13489)

One package including 6/8 boards

Package weight approximately 16,6 to 25kg, dependent on product selected

Packets are edge wrapped with cardboard and totally shrink wrapped with PE- membrane.

EAN (bar) code on the package

Production date/batch marking on backside of boards

QUALITY, SAFETY AND ENVIRONMENT

ISO 9001 Quality Management System Certificate and 14001 Environmental Management Certificate

Finnish RTS M1 emission classification and BREEAM-NOR

European E1 formaldehyde classification (EN 14342:2005) for construction materials:

Total emission of volatile organic compounds (TVOC) 0,011 mg/m²h

Emission of formaldehyde (ENV 717-1) < 0,004 mg/m²h

Company holds FSC and PEFC certifications

Products meet the requirements of class Dfl – s1 (EN 14342:2005 and EN 13501-1 part 1)

CE marking EN 14342:2005+A1 2008), see www.kareliaupofloor.com

