

**Resilient textile  
and laminated  
floor coverings**

Self-declaration that the named products comply with the requirements for resilient textile and laminated floor coverings as per BREEAM-NOR's chapter HEA 02

This form must be filled out by the MANUFACTURER of floor coverings according to EN 14041:2004.

Approved emission certificates are M1<sup>1</sup>, EC 1<sup>2</sup>, Gut, SINTEF Technical Approval or Nordic Ecolabel (Swan)<sup>3</sup>.

**If the product has one of the approved emission certificates, it is not necessary to fill in this form.** Connect the emission certificate to the product in goBIM.

<sup>1</sup> Approved performance standard NS-EN 15251:2007, Annex C

<sup>2</sup> Approved performance standard GEV Emicode

<sup>3</sup> Accepted except for wood or linoleum flooring

---

It is important that the information given here is correct, and we strongly encourage thoroughness in researching the extent to which emission testing and/or test reports show that the product complies with the standards and emission limit values required by BREEAM-NOR 2016. If in doubt, the manufacturer should consult own internal and external experts. **Providing incorrect and misleading information can have legal consequences. Once filled-out, the form must be signed by a legally responsible person for the manufacturer, such as a technical director or a managing director.**

MANUFACTURER:	ARTIGO SpA
PRODUCT TRADE NAME:	ND UNI
PRODUCT ID:	
INTENDED USE:	FLOORING

The following is hereby confirmed by the manufacturer:

1. The product is in accordance with product standard: EN 14041:2004.
2. The product has undergone an emission test<sup>3</sup> which shows that its emissions are below the values<sup>4</sup> shown in BREEAM-NOR 2016 "Table 15" according to the intended use of the product.

**Table 15:** Emission limits for all product categories – Conversion table

Emission	Wall		Floor/ceiling		Sealants	
	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3\text{h}$	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3\text{h}$	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3\text{h}$
TVOC 28d	200	417	200	160	4260	60
Formaldehyde 3d	24	50	62.5	50	3550	50
Formaldehyde 28d	50	104	50	40	710	10
Carcinogenic	5	10	5	4	71	1

<sup>3</sup>Documentation (test in acc. with approved standard) can be requested if required.

<sup>4</sup>Show accordance with units  $\mu\text{g}/\text{m}^3$  or  $\mu\text{g}/\text{m}^2\text{h}$

3. The emission test has been performed in accordance with the following approved standards ISO 16000-9 in combination with ISO 16000-6 (volatile organic compounds) and ISO 16000-3 (formaldehyde). Test and calculation shall be carried out according to EN 16516.

Legally responsible: R. GRILLO Position: Red Manager Date: 13/2/19

Signature: \_\_\_\_\_

