

HOMOGENEOUS
Semi Flexible Tiles



LRV 58

NCS S 1505-Y30R

Arran Beige **7420**



LRV 32

NCS S 4010-Y10R

Brecon Beige **7040***



LRV 47

NCS S 2010-Y40R

Durham Fawn **7400***



LRV 26

NCS S 5010-Y30R

Cambrian Bronze **7100**



LRV 48

NCS S 2020-Y20R

Cornish Cream **7370***



LRV 38

NCS S 3005-Y50R

Pennine Fawn **7030**



LRV 37

NCS S 3020-Y10R

Avon Sand **7080**



LRV 58

NCS S 2002-G50Y

Dover Grey **7330***



LRV 34

NCS S 3020-Y40R

Jersey Tan **7410***



LRV 50

NCS S 2502-Y

Border Grey **7110**



LRV 70

NCS S 1002-Y50R

Snowdrop **6010**



LRV 33

NCS S 3502-B


Pearl Grey **6130**



LRV 37

NCS S 3020-Y10R


Magnolia **6060***



LRV 11

NCS S 7010-Y50R

Walnut **6180***



LRV 8

NCS S 8005-Y80R

Dark Brown **6300**



LRV 5

NCS S 8502-R

Black Tulip **6040**



LRV 35

NCS S 3502-B

Mourne Grey **7310***



LRV 31

NCS S 4010-B10G

Lomond Grey **7320**



LRV 26

NCS S 5000-N

Firth Grey **7060***



LRV 45

NCS S 2010-B70G

Romney Green **7340**



LRV 30

NCS S 4010-G30Y

Cotswold Green **7010***



LRV 26

NCS S 3040-R90B

Lakeland Blue **7350***



LRV 48

NCS S 2010-Y80R

Wensley Beige **7390**



LRV 47

NCS S 2020-R40B

Mendip Mauve **7360**



LRV 20

NCS S 3040-R

Anglian Red **7380***

TRADITIONAL MARBLING †

DUOTONE MARBLING

*Also available in 1.5mm and 2.5mm guage.

NCS = Natural Colour System LRV = Light Reflectance Value
















† Colours include a secondary complimentary colour.

This decoration can only be appreciated by viewing a larger sample piece.

Polyflex Plus

Polyflex Plus PU is a durable, general purpose vinyl tile suitable for most contract situations. The excellent performance makes Polyflex Plus PU a good choice in schools, supermarkets and offices. The excellent performance of Polyflex Plus makes it a particularly suitable and economical solution for social housing refurbishment projects. With excellent durability, ease of maintenance and endless design possibilities, Polyflex Plus provides the ideal flooring solution to complement any interior design scheme.



	Gauge	EN 428/ISO 24346	1.5mm 2.0mm 2.5mm
	Tile Size	EN 427/ISO 24342	1.5mm: 300 x 300mm = 4.5m ² 2.0mm: 300 x 300mm = 4.5m ² 2.5mm: 300 x 300mm = 3.6m ²
	Total Weight	EN 430/ISO 23997	1.5mm: 2800g/m ² 2.0mm: 3800g/m ² 2.5mm: 4860g/m ²
	General Performance	EN 649 ISO 10581	Conforms Conforms
			1.5mm 
	Use Area	EN 685/ISO 10874	2.0mm 
			2.5mm 
	Reaction to Fire	EN 13501-1 ASTM E648	Class Bfl-S1 Class 1
	Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	Slip Resistance	EN 13893	Class DS
	Indentation Residual	EN 433/ISO 24343-1	<0.10mm
	Dimensional Stability	EN 434/ISO 23999	<0.25%
	Flexibility	EN 435/ISO 24344	(Method A) Pass 40mm mandrel
	VOC Emissions	Indoor Air Comfort GOLD	Eurofins certified product
<p>Environmentally Preferable Flooring - Polyflex Plus PU achieves a BRE Global Environmental Generic A+ rating. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflex Plus PU is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability</p>			
<p>PU - Polyflex Plus PU features a polyurethane surface treatment which provides an excellent foundation for an easy, ongoing maintenance regime.</p>			
	<p>For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com. Decoration and shade may vary slightly from the samples shown.</p>		

