

DECLARATION OF PERFORMANCE

Nr. DE0029/01

according Annex III of the Regulation (EU) No 305/2011

PCI Durapox[®] NT plus

1. Unique identification code of the product-type:

EN 12004 R2T

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Improved reaction resin adhesive with reduced slip

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**PCI Augsburg GmbH
Piccardstraße 11
D-86159 Augsburg**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

System 4 (for uses subject to reaction to fire regulations)

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified testing laboratory SFV Burgwedel, identification number 1212, performed the determination of the product-type on the basis of type testing under system 3 and issued: test report 77.670.401.101

The PCI Augsburg GmbH performed the classification regarding reaction to fire according to system 4 on the basis of resolution 2010/81/EU of the EU Commission

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance (PCI Durapox® NT plus)

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 12004:2007+A1:2012
Initial shear adhesion strength	≥ 2,0 N/mm ²	
Shear adhesion strength after water immersion	≥ 2,0 N/mm ²	
Shear adhesion strength after thermal shock	≥ 2,0 N/mm ²	
Dangerous substances	Comply with 4.5 (EN 12004)	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

.....
Clemens Bierig
managing director

.....
Manfred Grundmann
managing director

Augsburg, 22.04.2013