



Borskrue benyttes for feste av stålplater til tre. Skruene har minimum 20 µm elzink belegg og er pulverlakkert i ulike farger. 8 mm 6 kt. hode. Bruk 8 mm nutsetter eller 8 mm dybdestiller.

EGENSKAPER

EG
20 µm

OUTDOOR

Fordeler:

- 8 mm Sekskanthode
- Borspiss
- Lakkert
- EPDM pakning
- Elforzinket 20 µm

Farger:

- 75705 = sortlakkert RAL 9005
- 75708 = sortlakkert RAL 9005
- 75710 = sortlakkert RAL 9005
- 75706 = rødlakkert RAL 3009
- 75709 = rødlakkert RAL 3009
- 75704 = hvitlakkert RAL 9010
- 75707 = hvitlakkert RAL 9010





ANVENDELSE

Bruksområde:

- Stålplate til tre

TEKNISK DATA

Products dimensions



Art. nr.	Item code	NOBB nr.	Fastener dimensions [mm]					
			d	l	d _h	l _g	t _{fix}	bit
FARMZC4.8x20	75705 - 75704 - 75706	55838258 - 55842163 - 55836124	4.8	20	14	17	1	SW8
FARMZC4.8x35	75708 - 75707 - 75709	55838224 - 55838232 - 55836075	4.8	35	14	32	2	SW8
FARMZC4.8x60	75710	55836060	4.8	60	14	57	2	SW8

