

VERSION: 1.1 In acc. with the requirements of BREEAM-NOR 2016 version 1.1/02.05.2017

VVOOD PARQUET

Self-declaration that the named products comply with the requirements FLOORING AND for wood flooring and parquet as per BREEAM-NOR's chapter HEA 02

This form must be filled out by the MANUFACTURER of wood flooring and parquet according to EN 14342:2013

Approved emission certificates are M1¹ and EC 1².

If the product has one of the approved emission certificates, it is not necessary to fill in this form. Connect the emission certificate to the product in goBIM.

It is important that the information given here is correct, and we strongly encourage thoroughness in researching the extent to which emission testing and/or test reports show that the product complies with the standards and emission limit values required by BREEAM-NOR 2016. If in doubt, the manufacturer should consult own internal and external experts. Providing incorrect and misleading information can have legal consequences. Once filled-out, the form must be signed by a legally responsible person for the manufacturer, such as a technical director or a managing director.

MANUFACTURER:

STÖCKL GesmbH, A-3331 Kematen/Ybbs

PRODUCTTRADE NAME: B:hard Oak style

PRODUCTIDA

17930

The following is hereby confirmed by the manufacturer:

- 1. The product is in accordance with product standard: EN 14342:2013
- 2. The product has undergone an emission test³ which shows that its emissions are below the values⁴ shown in BREEAM-NOR 2016 "Table 15" according to the intended use of the product.
- 3. The manufacturer confirm the absence of regulated wood preservatives.

¹ Approved performance standard NS-EN 15251:2007, Annex C

² Approved performance standard GEV Emicode



VERSION: 1.1 In acc. with the requirements of BREEAM-NOR 2016

version 1.1/02.05.2017

Table 15: Emission limits for all product categories - Conversion table

Emission	\W	alli	Floor/Geiling		Sealants	
	µg/m²h	µg/m³h	μg/m²h	pg/m³h	µg/m²h	μg/m³h
TVOC 28d	200	417	200	160	4260	60
Formaldehyde 3d	24	50	62.5	50	3550	50
Formaldehyde 28d	50	104	50	40	710	10
Carcinogenic	5	10	5	4	71	1

³Documentation (test in acc. with approved standard) can be requested if required.

4. The emission test has been performed in accordance with the following approved standards ISO 16000-9 in combination with ISO 16000-6 (volatile organic compounds), ISO 16000-3 (formaldehyde). Test and calculation shall be carried out according to EN 16516.

Legally responsible: Georg Stöckl

Position: CEO

Signature:

STÖCKL GESMBH Heide, 25. Straße 1 A-3331 Kematen/Ybbs T +43/(0)7448/2178

F +43/(0)7448/2178-30 E office@stoeckl.com

www.stoeckl.com

Date: 12.12.2015

⁴Show accordance with units µg/m3 or µg/m2h