

Wood flooring/Parquet Self declaratrion on below product to be in accordance with the requirement to wood flooring/parquet according to BREEAM-NOR's topic HEA 9

This form must be completed by the **MANUFACTURER** of the wooden flooring/parquet flooring. If the

It is important that the information given here is correct, and we encourage the manufacturer to be thorough when checking if the emission tests and certificates of the product comply with the standards and emission levels that BREEAM-NOR require. If in doubt the manufacturer should consult with its own internal experts and resources and any external agencies that conduct testing and certification on behalf of the manufacturer.

The completed form must be signed by a legally responsible person from the manufacturer

MANUFACTURER:		NED It international, UAB			
NAME OF PRODUCT:		WOODlife Flooring			
DOCUEMNTATION			YES	NO	COMMENTS
REQUIREMENTS		RELEVANTE STANDARDS			
1.a	The product can be classified as E1 according to test method EN 717-1:2004	EN 14342:2005 EN 717-1:2004	X		
1.b	Or, we can confirm that no substance containing formaldehyde is added during production or any other process related to the product. Can be E1 classified without testing.	NS-EN 15251:2007 (Appendix C)			
2.	The product has an emission test documenting that emissions of TVOC are below <u>0,2 mg/m²h</u>	NS-EN 15251:2007 (Appendix C)	X		
3.	The product has an emission test documenting that emissions of formaldehyde are below <u>0,05 mg/m²h¹⁾</u>	NS-EN 15251:2007 (Appendix C)	X		

Bo Andren Norge AS
Lønghammarvegen 36
N-5536 Haugesund

S.W.M. Van Lieshout



4a.	The product has an emission test documenting that emissions of ammonia are below 0,03 mg/m²h ¹⁾²⁾	NS-EN 15251:2007 (Appendix C)	X		
4.b	Or, we can confirm following: 1) No traceable ammonia activity in the product And 2) No substance capable of cleaving to ammonia.				
5.	The product has an emission test documenting that emissions of carcinogenic substances (IARC) are below 0,005 mg/m²h ¹⁾	NS-EN 15251:2007 (Appendix C)	X		
6.	The product has an emission test documenting that odor dissatisfaction is below 15%	NS-EN 15251:2007 (Appendix C)	X		
7.	The emission tests in point 2-6 are conducted according to the ISO 16000-series, with emissions being measured after 28 days.	ISO 16000 (ISO 16000-3, -6, -9, -11)	X		
8.	The undersigned can confirm the absence of regulated wood preservatives and to be within the minimum levels.	NS-EN 14342:2005	X		

Name (Legal responsible):

Position:

Date:

A.W.M. Van Lieshart, Director

13-05-2014.

Signature:

