

MINIFIX



Type 4 – 8



Type 8 – 12



Type 4 – 18

Proven spacer for universal use. Clamping tongues for several bar diameters. Enlarged support increases tilting resistance. Open design which does not interrupt the concrete flow. Outside ribs featuring minor contact with formwork.

Art. No.	Type	Concrete cover (mm)	For bar Ø (mm)	Packaging (pcs.)
20238	5 / 4-6	5	4 - 6	5,000
20239	10 / 4-8	10	4 - 8	1,000
20240	12,5 / 4-8	12,5	4 - 8	1,000
20241	15 / 4-8	15	4 - 8	1,000
20242	15 / 8-12	15	8 - 12	1,000
20243	15 / 10-14	15	10 - 14	1,000
20244	15 / 14-18	15	14 - 18	1,000
20245	20 / 4-8	20	4 - 8	1,000
20246	20 / 4-18	20	4 - 18	1,000
20247	20 / 6-10	20	6 - 10	1,000
20248	20 / 8-12	20	8 - 12	1,000
20249	20 / 10-14	20	10 - 14	500
20250	20 / 12-16	20	12 - 16	500
20251	25 / 4-8	25	4 - 8	1,000
20252	25 / 4-18	25	4 - 18	1,000
20253	25 / 6-10	25	6 - 10	500
20254	25 / 10-14	25	10 - 14	500
20255	25 / 12-16	25	12 - 16	500
20256	25 / 16-20	25	16 - 20	500
20257	30 / 4-8	30	4 - 8	500
20258	30 / 4-18	30	4 - 18	500
20259	30 / 8-12	30	8 - 12	500
20260	35 / 5-10	35	5 - 10	500
20261	35 / 10-20	35	10 - 20	250
20262	40 / 4-8	40	4 - 8	500
20263	40 / 4-18	40	4 - 18	500
20264	40 / 8-12	40	8 - 12	500
20265	40 / 12-20	40	12 - 20	250
20266	40 / 20-30	40	20 - 30	250
20267	45 / 4-8	45	4 - 8	250
20268	45 / 4-18	45	4 - 18	250
20269	45 / 8-12	45	8 - 12	500
20270	50 / 4-10	50	4 - 10	250
20271	50 / 4-18	50	4 - 18	250
20272	50 / 8-12	50	8 - 12	250
20273	50 / 12-20	50	12 - 20	250
20274	60 / 4-18	60	4 - 18	250
20275	60 / 12-28	60	12 - 28	100
20276	70 / 12-20	70	12 - 20	100
20277	75 / 4-18	75	4 - 18	100
20278	75 / 4-18 Super	75	4 - 18	100
20279	75 / 20-26	75	20 - 26	100
20280	100 / 4-18	100	4 - 18	75
20281	100 / 12-32	100	12 - 32	75

Tested according to Specification „Abstandhalter“ [Spacers] DBV- o - L 1 of the German Association for Concrete and Construction Technology DBV