

Forbruk

Dimensjon Antall pr. eske Storpakk Nobb nr. Best. nr.

C6 FOR BETONG

20 mm	500 + 1 gass	10	46067961	057540
25 mm	500 + 1 gass	10	46068956	057541
30 mm	500 + 1 gass	10	46069005	057542
35 mm	500 + 1 gass	10	46069013	057543
40 mm	500 + 1 gass	10	46180286	057544



HC6 FOR HAR BETONG OG STÅL

15 mm	500 + 1 gass	10	46069024	057550
17 mm	500 + 1 gass	10	46073353	057551
22 mm	500 + 1 gass	10	46073364	057552
27 mm	500 + 1 gass	10	46073372	057553
32 mm	500 + 1 gass	10	46073398	057554



MONTERT MATERALTYKKELSE							
	0 - 5 mm	5 mm	10 mm	15 mm	20 mm	27 mm	
STÅL	HC6 15 mm	HC6 15 mm	HC6 17 mm	HC6 22 mm	HC6 27 mm	HC6 32 mm	HC6 15 mm
HARD BETONG	HC6 17 mm	-	HC6 22 - 27 mm	HC6 27 mm	HC6 32 mm	-	HC6 15 - 17 mm
BETONG OG TEGL	HC6 17 mm	HC6 22 - 27 mm	HC6 27 mm	HC6 32 mm	-	-	HC6 17 - 22 mm
BETONG OG TEGL	C6 20 - 25 mm	C6 25 mm	C6 25 - 30 mm	C6 35 mm	C6 35 - 40 mm	C6 40 mm	C6 25 mm

ANBEFALT LASTVERDI FOR HC6 - SKUDDSPIKER*:

Materiale	N Drag (kN)	V Tverr (kN)
Stål S 235 - Tykkelse minst 5 mm:	1.2	1.2
Betong C20/25:	0.25	0.25

STÅLTYKKELSE PÅ BASISMATERIALE:

Minimum = 5 mm
Anbefalt statisk/hvilende last = 120 kg

BETONG*:

Anbefalt statisk/hvilende last = 25 kg

*NB! Kun anbefalt, må testes i hvert enkelt tilfelle