



# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

P-statement(s)

H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H335: May cause respiratory irritation.

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
P233: Keep container tightly closed.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313: If eye irritation persists: Get medical advice/attention.  
P363: Wash contaminated clothing before reuse.  
P391: Collect spillage.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixture

Chemical characterization

Solution of an acrylic resin in (Meth-) acrylacidester

### Hazardous ingredients

Ingredient		Classification (EEC) No 67/548	Concentration
		Classification (EC) 1272/2008	
methyl methacrylate	CAS No.: 80-62-6 EC-No.: 201-297-1 Index-No.: 607-035-00-6 REACH No.: 01-2119452498-28-XXXX	F; R11 Xi; R37/38 R43	35.0 – 40.0 % by weight
		Flam. Liq. 2; H225 STOT SE 3; H335 Skin Irrit. 2; H315 Skin Sens. 1; H317	
Bisphenol A Epoxidharz, durchschnittl. MG >700- <1100		R43 Xi; R36/38	25.0 – 30.0 % by weight
		Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	
2-ethylhexyl acrylate	CAS No.: 103-11-7 EC-No.: 203-080-7 Index-No.: 607-107-00-7 REACH No.: 01-2119453158-37-XXXX	R43 Xi; R37/38	1.0 – 5.0 % by weight
		Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412	
1,1`-(p-Tolylimino)dipropan-2-ol	CAS No.: 38668-48-3 EC-No.: 254-075-1 REACH No.: 01-2119980937-17-XXXX	T; R25 Xi; R36 R52/53	0.1 – 1.0 % by weight
		Acute Tox. 2; H300 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice

Move out of dangerous area. Take off all contaminated clothing immediately. Do not leave the victim unattended. Show this safety data sheet to the doctor in attendance.

If inhaled

Move to fresh air. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

In case of skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation occurs, get medical advice/attention.

In case of eye contact

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed

Rinse mouth. Do NOT induce vomiting. Call a physician immediately.

## Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

### 4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention                      Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media                      Carbon dioxide (CO<sub>2</sub>), Foam, Water spray, Dry powder

Extinguishing media which must not be used for safety reasons                      High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases                      Violent polymerization may be caused by: Extremes of temperature and direct sunlight.  
Fire will produce dense black smoke containing hazardous combustion products (see heading 10). Exposure to decomposition products may be a hazard to health.

### 5.3 Advice for firefighters

Special protective equipment for firefighting                      In the event of fire, wear self-contained breathing apparatus.

Additional information on firefighting                      Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow run-off from fire fighting to enter drains or water courses.

## **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions                      Ensure adequate ventilation. Vapours are heavier than air and may spread along floors.  
Use personal protective equipment.

### 6.2 Environmental precautions

Environmental precautions                      Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up                      Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean contaminated surface thoroughly.

### 6.5 Additional information

Other information                      Treat recovered material as described in the section "Disposal considerations".

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling                      Processing may lead to evolution of flammable volatiles. In case of insufficient ventilation, wear suitable respiratory equipment. Keep product and empty container away from heat and sources of ignition.  
Handle and open container with care. Avoid contact with skin and eyes.

Precautions                      Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Observe label precautions.

Advice on protection against fire and explosion                      Take precautionary measures against static discharges. Vapours may form explosive mixture with air. Use water spray to cool unopened containers.

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

## 7.2 Conditions for safe storage, including any incompatibilities

Storage space and container requirements

Storage must be in accordance with the BetrSichV (Germany). Keep in a cool, well-ventilated place.

Keep in properly labelled containers. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

TRGS 510

3

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### METHYL METHACRYLATE

Netherlands

Long-term exposure value/ mg/m <sup>3</sup>	Short-term exposure value / mg/m <sup>3</sup>	Source
205	410	18

Source: 18 - Lijst met wettelijke grenswaarden 2011

Belgium

Long-term exposure value/ ppm	Long-term exposure value/ mg/m <sup>3</sup>	Short-term exposure value / ppm	Short-term exposure value / mg/m <sup>3</sup>	Source
50	208	100	416	35

Source: 35 - Liste de valeurs limites d'expositions professionnelle aux agents chimiques (11.06.2009)

Europe

Long-term exposure value/ ppm	Short-term exposure value / ppm	Issuing date	Source
50	100	2009/161	24

Source: 24 - DIRECTIVE 2009/161/EU

DNEL

Value	Target group	Exposure route	Exposure frequency	Source
210 mg/m <sup>3</sup>	Workers	Inhalation	Long term effects Local	100
210 mg/m <sup>3</sup>	Workers	Inhalation	Long term effects systemic	100
1,5 mg/cm <sup>2</sup>	Workers	dermal	Long term effects Local	100
13,67 mg/kg	Workers	dermal	Long term effects systemic	100
105 mg/m <sup>3</sup>	Consumers	inhale	Long term effects Local	100
74,3 mg/m <sup>3</sup>	Consumers	inhale	Long term effects, systemic	100
1,5 mg/cm <sup>2</sup>	Consumers	dermal	Long term effects Local	100
8,2 mg/kg	Consumers	dermal	Long term effects systemic	100
1,5 mg/cm <sup>2</sup>	Consumers	dermal	Short-term effects Local	100

Source: 100 - Firmendaten

PNEC

Value	Exposure route	Source
0,94 mg/l	freshwater	100
0,094 mg/l	marine water	100
5,74 mg/kg	sediment	100
1,47 mg/kg	Soil	100

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

Source: 100 - Firmendaten

## 2-ETHYLHEXYL ACRYLATE

### DNEL

Value	Target group	Exposure route	Exposure frequency	Source
37,5 mg/m <sup>3</sup>	Workers	Inhalation	Long term effects Local	100
0,242 mg/cm <sup>2</sup>	Workers	dermal	Long term effects Local	100
0,242 mg/cm <sup>2</sup>	Workers	dermal	Short-term effects Local	100
4,5 mg/m <sup>3</sup>	Consumers	inhale	Long term effects Local	100

Source: 100 - Firmendaten

### PNEC

Value	Exposure route	Source
0,002752 mg/l	fresh water	100
0,000272 mg/l	seawater	100
2,3 mg/l	wastewater treatment plant	100
0,126 mg/kg	sediment Water	100
0,126 mg/kg	sediment seawater	100
1,0 mg/kg	Soil	100
0,0023 mg/kg	intermittent releases	100

Source: 100 - Firmendaten

## 1,1`-(p-Tolylimino)dipropan-2-ol

### DNEL

Value	Target group	Exposure route	Exposure frequency	Source
2 mg/m <sup>3</sup>	Workers	Inhalation	Long term effects	100
0,6 mg/kg	Workers	dermal exposure	Long term effects	100

Source: 100 - Firmendaten

### PNEC

Value	Exposure route	Source
199,5	Waste water treatment	100
0,0072 mg/kg	marine water	100
0,017 mg/l	freshwater	100

Source: 100 - Firmendaten

## 8.2 Exposure controls

### Respiratory protection

Vapour during processing may be irritating to the respiratory tract and to the eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

### Remarks:

Recommended Filter type: A1, A2 (in case of higher concentration)

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

### Hand protection

Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

### Suitable material:

Nitriles

### Unsuitable material:

woven fabric, Leather gloves

## Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: **DERBITECH FLEX Primer AC 5 kg**

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

Break through time:	<25 min
Eye protection	Tightly fitting safety goggles
Skin and body protection	Wear suitable protective equipment. Long sleeved clothing
General protective and hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. Use protective skin cream before handling the product. Avoid contact with the skin and the eyes.
Engineering measures	Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

### **SECTION 9: Physical and chemical properties**

#### **9.1 Information on basic physical and chemical properties**

Physical state	liquid
Form	Liquid
Odour	typic for acrylates
Boiling point [°C]	appr. 100 °C
Flash point [°C]	10 °C
Evaporation rate [kg/(s*m <sup>2</sup> )]	not determined
Vapour pressure [kPa]	> 50 hPa
Temperature:	50 °C
Vapour density	not determined
Density [g/cm <sup>3</sup> ]	1,0-1,1 g/cm <sup>3</sup>
Temperature:	20 °C
Water solubility [g/l]	20 g/l
Partition coefficient n-octanol /water (log P O/W)	not determined
Explosive properties	Not relevant
Oxidising properties	Not relevant

#### **9.2 Other information**

Flow time [s]	appr. 45 – 60 sec
Temperature:	20 °C
Measuring method:	DIN cup 4 mm

### **SECTION 10: Stability and reactivity**

#### **10.3 Possibility of hazardous reactions**

Hazardous reactions	The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution. Risk of receptacle bursting.
---------------------	--

#### **10.4 Conditions to avoid**

Conditions to avoid	Extremes of temperature and direct sunlight.
---------------------	--

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

## 10.5 Incompatible materials

Materials to avoid

Reacts violently with peroxides. Reducing agents, Strong bases, Amines, Oxidizing agents

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Hazardous ingredients

##### METHYL METHACRYLATE

Oral toxicity [mg/kg]	Test criterion	Test species	Measuring method	Source
>5000	LD50	rat	OECD Test Guideline 401	100

Source: 100 - Firmendaten

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
>5000	LD50	rabbit	100

Source: 100 - Firmendaten

LC50 Inhalation 4h for vapours [mg/l]	Test criterion	Test species	Source
29,8 mg/l	LC50	rat	100

Source: 100 - Firmendaten

Irritant effect on skin	irritating
Test species	rabbit
Irritant effect on eyes	Irritant
Test species	rabbit
Sensitization	Skin sensitization
Test species	mouse
Carcinogenic effects	not a carcinogen
Test species	rat, mouse
Mutagenicity	not mutagenic
Reproduction toxicity	not toxic to reproduction

Specific target organ toxicity (single exposure) [mg/kg]	Source
Causes respiratory tract irritation.	100

Source: 100 - Firmendaten

Specific target organ toxicity (repeated exposure) [mg/kg]	Source
No known effect.	100

Source: 100 - Firmendaten

#### Bisphenol A Epoxidharz, durchschnittl. MG >700- <1100

Oral toxicity [mg/kg]	Test criterion	Test species	Source
5000 mg/kg	LD50	rat	100

Source: 100 - Firmendaten

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

## 2-ETHYLHEXYL ACRYLATE

Oral toxicity [mg/kg]	Test criterion	Test species	Source
4435 mg/kg	LD50	rat	100

Source: 100 - Firmendaten

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
7522 mg/kg	LD50	rabbit	100

Source: 100 - Firmendaten

Inhalative toxicity [mg/l]	Duration of dosage	Test species	Source
1,19 mg/l	8 hours	rat	100

Source: 100 - Firmendaten

Irritant effect on skin	Skin irritation
Test species	rabbit
Exposure duration	4 h
Irritant effect on eyes	slightly irritating
Measuring method	OECD Test Guideline 405
Test species	rabbit
Sensitization	Skin sensitization
Carcinogenic effects	No known effect.
Mutagenicity	No known effect.
Reproduction toxicity	No known effect.

Specific target organ toxicity (single exposure) [mg/kg]	Source
Causes respiratory tract irritation.	100

Source: 100 - Firmendaten

Specific target organ toxicity (repeated exposure) [mg/kg]	Source
No known effect.	100

Source: 100 - Firmendaten

## 1,1`-(p-Tolylimino)dipropan-2-ol

Oral toxicity [mg/kg]	Test criterion	Test species	Source
45 mg/kg	LD50	rat	2

Source: 2 - SimChem

Dermal toxicity [mg/kg]	Test criterion	Test species	Source
2001 mg/kg	LD50	rat	2

Source: 2 - SimChem

Irritant effect on skin	No skin irritation
Irritant effect on eyes	Irritant
Sensitization	No sensitization responses were observed.
Mutagenicity	negative



# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

## 11.2 Additional information

Experience in practice

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes, respiratory system and skin. Irritating to mucous membranes

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Hazardous ingredients

##### METHYL METHACRYLATE

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Measuring method	Source
191 mg/l	LC50	Oncorhynchus mykiss (rainbow trout)	96 h	OECD Test Guideline 203	100

Source: 100 - Firmendaten

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Measuring method	Source
69 mg/l	EC 50	Daphnia magna (Water flea)	48 h	OECD Test Guideline 202	100

Source: 100 - Firmendaten

Toxicity to algae [mg/l]	Test criterion	Test species	Exposure duration	Measuring method	Source
>110 mg/l	EC 50	Selenastrum capricornutum (green algae)	72 h	OECD Test Guideline 201	100

Source: 100 - Firmendaten

NOEC (fish) [mg/l]	Test species	Measuring method	Source
9,4	Brachydanio rerio (zebra fish)	OECD Test Guideline 210	100

Source: 100 - Firmendaten

NOEC (daphnia) [mg/l]	Test species	Measuring method	Source
37	Daphnia magna (Water flea)	OECD Test Guideline 202	100

Source: 100 - Firmendaten

Biodegradability

Readily biodegradable.

Method of analysis

OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F

Bioaccumulation

Does not bioaccumulate.

Mobility

Mobility

Terrestrial Compartment Not relevant

##### 2-ETHYLHEXYL ACRYLATE

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Measuring method	Source
1,81	LC50	Oncorhynchus mykiss (rainbow trout)	96 h	OECD Test Guideline 203	100

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

Source: 100 - Firmendaten

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Measuring method	Source
1,3	EC 50	Daphnia magna (Water flea)	48 h	OECD Test Guideline 202	100

Source: 100 - Firmendaten

Toxicity to algae [mg/l]	Test criterion	Test species	Exposure duration	Measuring method	Source
1,71	ErC50	Desmodesmus subspicatus	72 h	OECD Test Guideline 201	100

Source: 100 - Firmendaten

NOEC (algae) [mg/l]	Test species	Measuring method	Source
0,45	Desmodesmus subspicatus	OECD Test Guideline 201	100

Source: 100 - Firmendaten

Biodegradability Readily biodegradable.

Bioaccumulation Bioaccumulation slight, log Pow 4,64

## 1,1`-(p-Tolylimino)dipropan-2-ol

Toxicity to fish [mg/l]	Test criterion	Test species	Exposure duration	Source
17	LC50	Brachydanio rerio (zebra fish)	96 h	2

Source: 2 - SimChem

Toxicity to daphnia [mg/l]	Test criterion	Test species	Exposure duration	Source
28,8	EC 50	Daphnia magna (Water flea)	18 h	100

Source: 100 - Firmendaten

Toxicity to algae [mg/l]	Test criterion	Test species	Exposure duration	Source
245	EC 50	Desmodesmus subspicatus	27 h	2

Source: 2 - SimChem

Biodegradability Poorly biodegradable.

Bioaccumulation no data available

## 12.5 Results of PBT and vPvB assessment

Results of PBT characteristics determination This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

## 12.6 Other adverse effects

Further information on ecology We have no quantitative data concerning the ecological effects of this product.

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Disposal considerations

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The following Waste Codes are only suggestions:

Waste Code

08 04 10: waste adhesives and sealants other than those mentioned in 08 04 09 The EWC Nr. only apply for the liquid product.

08 01 12: waste paint and varnish other than those mentioned in 08 01 11 The EWC Nr. only apply for the liquid product.




17 02 03: plastic This EWC Nr. only apply for the hardened product.

08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

Uncleaned empty packaging

-  
-

## SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1263	1263	1263
14.3 Transport hazard class(es)	3	3	3
14.4 Packaging group	III	III	III
14.2 Description of the goods	PAINT	PAINT	PAINT
14.2 UN proper shipping name		PAINT	Paint
Remarks	(einschließlich Farbe, Lack, Emaille, Beize, Schellack, Firnis, Politur, flüssiger Füllstoff und flüssige Lackgrundlage)	(including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base)	(including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
Labels	3 	3 	3 - Flammable Liquid 
Risk No.	30		
Category	3		
Factor	1		
Classification Code	F1		
SP 640	640E		
Tunnel restriction code	D/E		
EmS		F-E;_S-E	
Stowage category		A	

### 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Additional regulations

Denmark PR-No.2400391

Denmark MAL-Code-Number 4-5

Additionally, observe any national regulations!

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: DERBITECH FLEX Primer AC 5 kg

Article-No.: 22220-000-125-C

Revision date: 23.03.2015

Version: 3/en



Print date: 10.06.2015

## SECTION 16: Other information

Relevant R-phrases R11: Highly flammable.  
R25: Toxic if swallowed.  
R36: Irritating to eyes.  
R36/38: Irritating to eyes and skin.  
R37/38: Irritating to respiratory system and skin.  
R43: May cause sensitisation by skin contact.  
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Relevant H-phrases H225: Highly flammable liquid and vapour.  
H300: Fatal if swallowed.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H335: May cause respiratory irritation.  
H412: Harmful to aquatic life with long lasting effects.

Wording of the hazard classes Flam. Liq.: Flammable liquid  
STOT SE: Specific target organ toxicity – single exposure  
Skin Irrit.: Skin irritation  
Skin Sens.: Skin sensitization  
Eye Irrit.: Serious eye irritation  
Aquatic Chronic: Hazardous to the aquatic environment  
Acute Tox.: Acute toxicity

Modifications since last version Modifications of the previous version are denoted with an asterisk (\*).

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

Classification	evaluation
Flam. Liq. 2; H225	
Skin Irrit. 2; H315	
Eye Irrit. 2; H319	
Skin Sens. 1; H317	
STOT SE 3; H335	
Aquatic Chronic 2; H411	

Department issuing safety data sheet Environmental Department

Further information Full text of R-phrases referred to under sections 2 and 3