

SPIT PULSA 800 INSULFAST



In accordance to:
 EN 12549
 EN ISO 11148-13
 Directive tool:
 2006/42/EC
 2011/65/UE
 1999/5/EC
 CEM 2004/108/EC
 Fuel cell: 75/324/EC
 Battery: 2006/66/EC
 Charger: 2006/95/EC
 CEM 2004/108/EC

Tool specifications	
Name	SPIT PULSA 800 INSULFAST
Impact force (Joules)	82
Weight (kg)	3,6 kg (with battery)
Overall dimension LxH (mm)	544x114x309
Energy	Fuel cell & Battery
Fastener lengths (mm)	60 to 200 mm

Characteristics
Fully automatic tool (1000 shots per hour)
Low push down force (4.5 kg)
Gas & Battery gauges: check gas & battery levels anytime
Start & Go system: energy saving, "self cut-off" when it is not used for 1mn
Automatic gas dosage (used T° - 5 °C to + 49 °C)
Battery charging time: 90 mn (25 mn = 500 pins)
Fuel cell: 750 shots (20 °C), battery: up to 3000 shots

Safety specifications
CE marking
Complete tool pressure necessary to generate the shot
Security with on / off led indicator
Noise level, EN 12549 : LpA,1s,1m=96dB(A) / Lp Cpeak=135 dB (C)
Vibration, EN ISO 8662-11 : 5,3 m·s ⁻²

Accessories	Consumables
Cleaning kit	IF pins