Golvfärg Plus



Highest quality Resistant to wear Gentle on both people and environment

Let your home be like new with a newly painted floor. Beckers Golvfärg Plus is a glossy floor paint of the highest quality that is used on concrete floors indoors. The paint contains no strong solvents and is therefore gentle on both you and the environment. The paint is easy to apply and gives a sustainable, covering end result.

Technical information

USE

Universal

COVERAGE

8 - 10 m²/l

GLOSS

Gloss

TOOLS

Brush, roller

PAINTING TEMPERATURE

Between +5°C to ca. +25°C surface temperature

DRYING TIME AT +23°C AND 50% RH

Tack-free after 1 hrs. Recoat after 3 hrs.

BINDER

Acrylate

VOC

Limit (Kat A/i): 140 g/l (2010). Product's VOC < 140 g/l.

For latest version: www.beckers.se



Store above freezing





ersion 20072

Preparation

NEW PAINTING UNPAINTED CONCRETE FLOORS, AT LEAST 1 MONTH OLD: clean from dirt and dust. Grease and oil stains shall be washed off with Beckers Avfettning. Any cement skin shall be removed by machine grinding or pickling with hydrochloric acid -1 part hydrochloric acid to 4 parts water. Rinse well with water. PLEASE NOTE! Be very careful when handling hydrochloric acid. When the floor has dried, prime once with Golvfärg Plus diluted with 10% water.

REPAINTING PREVIOUSLY PAINTED OR LACQUERED CONCRETE SURFACES: Spray on Beckers Inomhustvätt and let the foam work for a few minutes, then wipe the surface with a damp microfibre cloth. Matte sand glossy surfaces with medium-fine abrasive paper. The floor gets its full durability and can be loaded on after 3 days. PAINTING OF LINOLEUM MATTING: Clean the floor thoroughly with Beckers Inomhustvätt and scourer (e.g. green Scotch-Brite) and dry thoroughly with clean lukewarm water several times to remove wax and polish residue. A test painting of a small area is recommended to ensure that the floor is free of waxes and polish and has good adhesion.

Painting

For best results finish with 1-2 coats of Golvfärg Plus undiluted.

Care instructions

Everyday care

Vacuum or dry mop the floor. For wet drying, use a well-wrung cloth / mop and an all-purpose cleaner or detergent. PLEASE NOTE! Never use alcohol, stronger detergents or wax cleaning agents.

Touching up / complementary treatment
Clean the floor thoroughly and grind the surface with a fine abrasive paper. Always touch up with the same product that the surface was last painted with and if possible the same batch number as last used. If another batch number is used or with a subsequent application of paint a slight colour difference may occur. For best results always paint the floor to avoid

structural, colour and gloss differences. When staining improves, try to follow the floor colour structure/grain/brush strips in order to minimise the risk of structural, colour and gloss differences.

Other matters

Normally, the floor can begin to be used after 1-2 days. Before that, care should be taken with the treated floor. For heavier loads on the floor, e.g. a sofa or cabinet, the floor should be allowed to dry for 5 days for full curing of the paint film. Drying times indicated are for normal temperature and humidity on the floor, 23°C and 50% humidity. At colder surfaces and higher humidity, drying time is prolonged.

Important

Do not paint on surfaces with a temperature lower than +5 °C. Stir well from the bottom before use.

For more information, read our work advice, fact sheets, brochures and website.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

