

## DECLARATION OF PERFORMANCE N° P352A-V1-EN

1 - Unique identification Code of the product type:  
**P352A-RESIDEK N3**

2 - Identification of the construction product, in accordance with article 11(4)  
RESIDEK N3/ Lot number: see on product or on labelling: see product packaging

3 - Intended use(s) of the construction product:  
Reinforced bituminous sheet for roof waterproofing

4 - Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with article 11(5):  
DERBIGUM-IMPERBEL sa/nv, Chaussée de Wavre, 67 B-1360 Perwez (België)

5 - Name and contact address of authorised representative in accordance with article 12(2):  
Not applicable

6 - System(s) of assessment and verification of constancy of performance of the product as set out in Annex V  
AVCP 2+ / AVCP 3 and/or AVCP 4

7 - In case of the declaration of performance concerning a construction product covered by a harmonised standard :  
-In case of AVCP2+, BCCA- Belgian Construction Certification Association (Notified Body n°0749) :  
- performed the inspection of the factory production control under system 2+  
- and issued certificate of conformity of the factory production control  
n° BC2-310-0305-0123-01

8 - In case of the declaration of performance concerning a construction product for which a European technical assessment has been issued:  
Not applicable

# RESIDEK®

9 – Declared performances following harmonized technical specification  
**EN 13707 : 2004 + A2 : 2009**

Essential characteristics	Performances	Units
External fire performance (Note 1)	FRoof	-
Reaction to fire	F	-
Watertightness	Pass	-
Tensile strength : Maximum tensile force LxT* Elongation at maximum tensile force LxT*	800 x 700 (± 20%) 30 x 30 (± 15)	N/50 mm %
Root Resistance	NPD**	-
Resistance to static loading method A	10	kg
Resistance to impact method A and B	1000	mm
Resistance to tearing LxT*	≥250	N
Joint strength : Peel resistance Shear resistance	NPD** NPD**	N/50 mm N/50 mm
Durability : UV Heat and water Heat flow after heat oven exposure	NPD** NPD**	- °C
Pliability	-20	°C
Dangerous Substances	(Note 2)	-

\* L means longitudinal direction, T means transverse direction

\*\*NPD No Performance Declared

Note 1: No performance can be given. The external fire performance of a roof is dominated by the built up system

Note 2: In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use

10 – The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:



Mr Steve Geubels,  
Group Operations Director

Perwez , 22/08/2018