



ALL MATS CO., LTD.

No.2, Dong Yuan Rd., Zanan Industrial Zone,
Liu He Town, Tai Cang City, Jiang Su Province, China
TEL: 86-512-53600780 FAX: 86-512-53600783
Zip code: 215431 E-mail: allmats@allmats.com.cn

All Mats R&D Test Report

Debris Trap Property Test

Test Sample: Debris Trap

Test Date: 2008.5.12

Test Requested: Test the debris trap property

Test Method:

Test Results: Please refer to the next page

All Mats R&D

Lucy Sheng (Authorized Signature)

Debris Trap Property Test Report

Test Result:

PRODUCT NAME	DEBRIS TRAP	
MANUFACTURED BY	ALL MATS CO., LTD	
Manufacturing Process	100% Virgin PVC Injection Tiles (Roll form available)	
Surface Aspect	Open construction vinyl grid with extra star textured shape for all direction anti-slip	
PRODUCT DIMENSIONS		
Thickness	1/2"	
Modular Size	12" × 18"	
Custom Size	Modules can be put together to form custom sizes	
PRODUCT PROPERTIES		
Appearance	Textured surfaced, giving slip resistant properties	
Ultra Violet Light (UV)	Resistance to PVC degradation (fully pigmented)	
Workability	Flexible PVC, easy to pick up for cleaning. Trim to fit on site	
Structural Integrity	MAX TEAR FORCE 300KG/SQUARE METER	
Acoustic	Excellent sound absorption	
Chemical	Non-porous PVC with Nitride rubber blend-inhibits the growth of bacteria. Resistant to most acids, alkaline and oils.	
Slip Resistant	DIN 51130	R 13 CLASSIFICATION
FLAMMABILITY RATING	UL 94	V0
Flooring Radiant Panel Test	ASTM E648/DIN 4102/CPSCFF1-70	Passes Federal Flammability Standard
Electrical Resistance		Gateway 12,000 volts