



## 4-in-1 Moulding

### Description:

- Four needs – one solution!
- Patented innovation by Pergo
- Perfectly matched in colour and structure
- Very high wear (AC5)





T-moulding:  
From laminate to laminate



Carpet transition:  
From laminate to carpet



Hard surface reducer:  
From laminate to ceramic,  
vinyl or linoleum



End moulding:  
Finishing up to thresholds,  
sliding doors etc

### Characteristics:

Properties	Value
Surface material	Flooring Laminate (HPL)
Wear resistance	AC5 (heavy commercial use)
Scratch resistance	TitanX™ surface
Surface texture	Matched to the floor
Core material	HDF, moisture resistant
Bottom part	Galvanised iron. Screws (3,5x 25 mm) and plugs (Ø5) included

### Demographics:

Product	Length mm	Width mm	Height mm	Quantity/pack pcs
T-moulding, 370xx	2000	43	3*	3
Carpet transition, 370xx	2000	44	3*	3
Hard surface reducer, 370xx	2000	51	3*	3
End moulding, 370xx	2000	44	3*	3

\*over flooring surface

### Installation instruction:

Suitable for floors between 7-12 mm

Screw the metal track to the subfloor and snap-in the moulding into place.

In case of under floor heating consider fix the profile by gluing

A detailed installation instruction is included in the product package.

Please Note: Specifications and features in this TDS could be subject to change without notice!