

Product Description

- **Dimensions** 12,30 x 30,30 x 2400 mm (0,61 kg).
- **Packaging** 10 end-profiles / tube (100 x 2440 mm / 12,67 kg).
7 tubes / pallet (87,70 kg) (= 70 pieces / pallet).
- **Labelling** Per piece.
- **Composition** MDF (for detailed composition please view table technical data).
- **Decor** BerryAlloc decors.
- **Installation** Install with included tracks, plugs and screws:
 - 1) Cut the track & profile into the proper width.
 - 2) Indicate drilling holes.
 - 3) Drill holes and install plugs in the subfloor.
 - 4) Place track, insert screws through track holes.
 - 5) Click the profile into the installed track.

Technical specifications

Core	Type Quality Thickness Density Internal bond dry Bending strength Modulus of elasticity Thickness swelling in 24 h	MDF V313 moisture resistant 12 mm 600 +30 kg/m ³ 0.45N/mm ² 20N/mm ² 1700 /mm ² 16,0%	EN 323 EN 319 EN 310 EN 310 EN 317
Glue	Type Heat resistance Moisture resistance	PUR hotmelt Tested up to 150 °C High	
Wrapping	CPL Thickness Wear resistance Heat resistance (180°C) Impact resistance (N) Scratch resistance (N) Light Fastness	According to EN 438 and EN13329 0,3 mm (tolerance +/- 0,05) AC3 (EN 13329) OK ≥ 10 ≥ 1.5N > 4	

