

NorGeoSpec 2012 Product Certificate



Certificate no.: 2402-QC-1462
Date: 06.03.2015
Valid until: 05.03.2017

Manufacturer: Fibertex Nonwovens A/S
Product: F-34
Product Type: GTX-N

Raw material: PP
Function: Separation and Filtration

Quality Product Certification Separation and Filtration

Characteristic	Standard	Unit	Declared value	Max. tolerance	Certification value	
Mass per unit area	EN ISO 9864	g/m ²	190	± 19	171-209	
Mechanical tests						
Tensile strength	MD	EN ISO 10319	kN/m	15.00	- 1.50	15.03
	CMD	EN ISO 10319	kN/m	18.40	- 1.84	
Elongation at max. load	MD	EN ISO 10319	%	40.0	- 8.0	32.0
	CMD	EN ISO 10319	%	40.0	- 8.0	
Static puncture test	EN ISO 12236	kN	2.500	- 0.250	2.250	
Dynamic perforation resistance	EN ISO 13433	mm	22	+ 4	26	
Energy Index	NorGeoSpec 2012	kN/m	3.2	-	3.2	
Hydraulic tests						
Velocity Index	EN ISO 11058	m/s	0.040	- 0.012	0.028	
Characteristic opening size	EN ISO 12956	µm	75	± 23	52-98	
Durability (Declared value)						
Service life		years	25			

Quality Product Specification

Separation and Filtration

Application profile: 3

Issued by

Christian Recker, NorGeoSpec project manager

Approved by

Arnstein Watn, Head of the Technical committee



The products are regularly audited and tested to verify that the characteristics fulfil the NorGeoSpec requirements.
Approved by the NorGeoSpec Technical committee: 06.03.2015