





<b>BESKRIVELSE</b>			
Total tykkelse	EN 428	mm	2.40
Tykkelse slitesjikt	EN 429	mm	2.4
Vekt	EN 430	g/m <sup>2</sup>	3400
Flisstørrelse	EN 427	cm	30.5 x 61
Antall fliser/pakke	-	-	20
<b>KLASSIFISERING</b>			
Norm	-	-	EN 649
Europaklasse	EN 685	-	34 - 43
Brannklassifisering	EN 13 501-1	klasse	Bfl-s1
Elektrostatisk oppladning	EN 1815	kV	< 2
Friksjon, våt	DIN 51 130	klasse	R10
<b>TESTVERDIER</b>			
Slitestyrke	EN 660.2	mm <sup>3</sup>	≤ 4.0
Slitasjegruppe	EN 649	gruppe	P
Type Binder content	ISO 10582	type	II
Dimensjonsstabilitet	EN 434	%	≤ 0.25
Inntrykksfasthet	EN 433	mm	≤ 0.10
Trinnlydsdemping	EN ISO 717-2	dB	4
Romlyd	NF S 31074	dB	76
Rullende stolhjul (typen W)	EN 425	-	OK
Varmemotstand	EN 12524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Overflatebehandling	-	-	PUR+
Kjemikaliebestandighet	EN 423	klasse	OK
<b>CE MARKING</b>			
	EN 14041	-	  
		-	