






BESKRIVELSE			
Total tykkelse	EN 428	mm	6.00
Tykkelse slitesjikt	EN 429	mm	2
Vekt	EN 430	g/m ²	9380
Flisstørrelse	EN 427	cm	63.5 x 63.5 65 x 65*
KLASSIFISERING			
Norm	-	-	EN 649
Europaklasse	EN 685		34 - 43
Brannklassifisering	EN 13 501-1	klasse	B _{fl} -s1
Elektrostatisk oppladning	EN 1815	kV	< 2
Friksjon, våt	DIN 51130	klasse	R10
TESTVERDIER			
Slitestyrke	EN 660.2	mm ³	≤ 2
Slitasjegruppe	EN 649	gruppe	T
Type Binder content	ISO 10582	type	I
Dimensjonsstabilitet	EN 434	%	≤ 0.25
Inntrykksfasthet	EN 433	mm	≤ 0.10
Kant stivhet	EN ISO 868	H _D	≥ 55
Rullende stolhjul (typen W)	EN 425	-	OK
Varmemotstand	EN 12524	W/(m.K)	0.25
Fargebestandighet	EN 20 105 - B02	skala	≥ 6
Overflatebehandling	-	-	PUR+
Kjemikaliebestandighet	EN 423	-	OK
CE MARKING			
	EN 14041	-	  
		-	 B _{fl} -s1

* upon request